



A Textron Company

# Owner's Guide



# 622012

**ISSUED JULY 2011**

**REVISED APRIL 2014**

# WELCOME

Thank you for purchasing this vehicle. Before driving the vehicle, we ask you to spend some time reading this Owner's Guide. This guide contains the information that will assist you in maintaining this highly reliable vehicle. Some illustrations may show items that are optional for your vehicle. This guide covers the operation of several vehicles; therefore, some illustrations may not represent your vehicle. Physical differences in controls will be illustrated.

Most of the service procedures in this guide can be accomplished using common, automotive hand tools. Contact your service representative on servicing the vehicle in accordance with the Periodic Service Schedule.

Repair or replacement parts are available through your E-Z-GO retailer or E-Z-GO Genuine Service Parts.

**The following information is needed when contacting E-Z-GO concerning service or parts for your vehicle:**

**Vehicle Model** \_\_\_\_\_

**SERIAL Number / PIN Number / VIN Number** \_\_\_\_\_

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## OWNER'S GUIDE GASOLINE POWERED VEHICLE

**TERRAIN 250**

**STARTING MODEL YEAR 2012**

Never modify the vehicle in any way that will alter the weight distribution of the vehicle, decrease its stability or increase the speed beyond the factory specifications. Such modifications can cause serious personal injury or death. E-Z-GO Division of Textron, Inc. prohibits and disclaims responsibility for any such modifications or any other alteration which would adversely affect the safety of the vehicle.

E-Z-GO Division of Textron, Inc. reserves the right to incorporate engineering and design changes to products in this manual, without obligation to include these changes on units sold previously.

The information contained in this manual may be revised periodically by E-Z-GO Division of Textron, Inc., and therefore is subject to change without notice.

E-Z-GO Division of Textron, Inc. **DISCLAIMS LIABILITY FOR ERRORS IN THIS MANUAL**, and **SPECIFICALLY DISCLAIMS LIABILITY FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES** resulting from the use of the information and materials in this Manual.

These are the original instructions as defined by 2006/42/EC.

### TO CONTACT US

E-Z-GO Division of Textron Inc.

1451 Marvin Griffin Road.

Augusta, Georgia, USA 30906-3852

North America:

Technical Assistance & Warranty PHONE: 1-800-774-3946 FAX: 1-800-448-8124

Service Parts PHONE: 1-888-GET-EZGO (1-888-438-3946) FAX: 1-800-752-6175

International PHONE: 001-706-798-4311 FAX: 001-706-771-4609

# FOREWORD

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

**This vehicle has been designed and manufactured in the United States of America (USA) as a 'World Vehicle'. The Standards and Specifications listed in the following text originate in the USA unless otherwise indicated.**

**The use of non Original Equipment Manufacturer (OEM) approved parts may void the warranty.**

**Overfilling battery may void the warranty.**

**Tampering with or adjusting the governor to permit vehicle to operate at above factory specifications will void the vehicle warranty.**

**When servicing engines, all adjustments and replacement components must be per original vehicle specifications in order to maintain the United States of America Federal and State emission certification applicable at the time of manufacture.**

## **BATTERY PROLONGED STORAGE**

**All batteries will self discharge over time. The rate of self discharge varies depending on the ambient temperature and the age and condition of the batteries.**

**A fully charged battery will not freeze in winter temperatures unless the temperature falls below -75°F (-60°C).**

## **BATTERY DISPOSAL**

**Lead-acid batteries are recyclable. Return whole scrap batteries to distributor, manufacturer or lead smelter for recycling. For neutralized spills, place residue in acid-resistant containers with absorbent material, sand or earth and dispose of in accordance with local, state and federal regulations for acid and lead compounds. Contact local and/or state environmental officials regarding disposal information.**

# TABLE OF CONTENTS

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

| SECTION                         | PAGE NO.     |
|---------------------------------|--------------|
| SAFETY.....                     | 1-1          |
| GENERAL SPECIFICATIONS.....     | 2-1          |
| INTRODUCTION.....               | 3-1          |
| OPERATING PROCEDURES.....       | 4-1          |
| MAINTENANCE.....                | 5-1          |
| DECLARATION OF CONFORMITY ..... | APPENDIX A-1 |

# TABLE OF CONTENTS

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## Notes:

Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.

| TITLE                                          | PAGE NO. |
|------------------------------------------------|----------|
| SAFETY .....                                   | 1-3      |
| NOTICES, CAUTIONS, WARNINGS, AND DANGERS ..... | 1-3      |
| GENERAL .....                                  | 1-5      |
| GENERAL OPERATION .....                        | 1-5      |
| MAINTENANCE .....                              | 1-6      |
| VENTILATION .....                              | 1-6      |
| LABELS AND PICTOGRAMS .....                    | 1-7      |

# SAFETY

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## 1 Notes:

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## SAFETY

For any questions on material contained in this manual, contact an authorized representative for clarification.


Read and understand all labels located on the vehicle. Always replace any damaged or missing labels.

On steep hills it is possible for vehicles to coast at greater than normal speeds encountered on a flat surface. To prevent loss of vehicle control and possible serious injury, speeds should be limited to no more than the maximum speed on level ground. See GENERAL SPECIFICATIONS. Limit speed by applying the service brake.

Catastrophic damage to the drivetrain components due to excessive speed may result from driving the vehicle above specified speed. Damage caused by excessive speed may cause a loss of vehicle control, is costly, is considered abuse and will not be covered under warranty.

Use extra caution when towing the vehicle(s). Do not tow a single vehicle at speeds in excess of 12 mph (19 kph). Do not tow more than three vehicles at a time. Do not exceed 5 mph (8 kph) while towing multiple vehicles. Towing the vehicle at above the recommended speed may result in personal injury and/or damage to the vehicle and other property. Vehicles equipped with the AC Drive motor must be towed with the Run-Tow switch, located under the passenger seat, in the 'Tow' position.

If the vehicle is to be used in a commercial environment, signs similar to the ones illustrated should be used to warn of situations that could result in an unsafe condition.



Observe these **NOTICES, CAUTIONS, WARNINGS** and **DANGERS**; be aware that servicing a vehicle requires mechanical skill and a regard for conditions that could be hazardous. Improper service or repair may damage the vehicle or render it unsafe.

## NOTICES, CAUTIONS, WARNINGS, AND DANGERS

Throughout this guide **NOTICE, CAUTION, WARNING**, and **DANGER** will be used. Please observe these **NOTICES, CAUTIONS, WARNINGS**, and **DANGERS**; be aware that servicing a vehicle requires mechanical skill and a regard for conditions that could be hazardous. Improper service or repair may damage the vehicle or render it unsafe.

### NOTICE

*Address practices not related to personal injury.*



### CAUTION

*Indicates a hazardous situation which, if not avoided, could result in minor or moderate injury.*



### WARNING

*Indicates a hazardous situation which, if not avoided, could result in death or serious injury.*



### DANGER

*Indicates a hazardous situation which, if not avoided, will result in death or serious injury.*

# SAFETY

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

1



## WARNING

**Engine exhaust from this product contains chemicals known, in certain quantities, to cause cancer, birth defects, or other reproductive harm.**

## NOTICE

*The exhaust emissions of this vehicles' engine complies with regulations set forth by the Environmental Protection Agency (EPA) of the United States of America (USA) at time of manufacture. Significant fines could result from modifications or tampering with the engine, fuel, ignition or air intake systems*



## WARNING

**Battery posts, terminals and related accessories contain lead and lead compounds. Wash hands after handling.**

## NOTICE

*This spark ignition system meets all requirements of the Canadian Interference-Causing Equipment Regulations.*

This manual has been designed to assist in maintaining the vehicle in accordance with procedures developed by the manufacturer. Adherence to these procedures and troubleshooting tips will ensure the best possible service from the product. To reduce the chance of personal injury or property damage, the following must be carefully observed:



## CAUTION

*Certain replacement parts can be used independently and/or in combination with other accessories to modify an E-Z-GO-manufactured vehicle to permit the vehicle to operate at or in excess of 20mph. When an E-Z-GO-manufactured vehicle is modified in any way by the Distributor, Dealer or customer to operate at or in excess of 20mph, UNDER FEDERAL LAW the modified product will be a Low Speed Vehicle (LSV) subject to the strictures and requirements of Federal Motor Vehicle Safety Standard 571.500. In these instances, pursuant to Federal law the Distributor or Dealer MUST equip the product with headlights, rear lights, turn signals, seat belts, top, horn and all other modifications for LSV's mandated in FMVSS 571.500, and affix a Vehicle Identification Number to the product in accordance with the requirements of FMVSS 571.565. Pursuant to FMVSS 571.500, and in accordance with the State laws applicable in the places of sale and use of the product, the Distributor, Dealer or customer modifying the vehicle also will be the Final Vehicle Manufacturer for the LSV, and required to title or register the vehicle as mandated by State law.*

E-Z-GO will NOT approve Distributor, Dealer or customer modifications converting E-Z-GO products into LSV's.

The Company recommends that all E-Z-GO products sold as personal transportation vehicles BE OPERATED ONLY BY PERSONS WITH VALID DRIVERS LICENSES, AND IN ACCORDANCE WITH APPLICABLE STATE REQUIREMENTS. This restriction is important to the SAFE USE AND OPERATION of the product.

All customers should adhere to this SAFETY RESTRICTION, in connection with the use of all E-Z-GO products, new and used, the Distributor or Dealer has reason to believe may be operated in personal transportation applications.

Information on FMVSS 571.500 can be obtained at Title 49 of the Code of Federal Regulations, section 571.500, or through the Internet at the website for the U.S. Department of Transportation - at Dockets and Regulation, then to Title 49 of the Code of Federal Regulations (Transportation)

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## GENERAL

All vehicles can be used for a variety of tasks beyond the original intended use of the vehicle; therefore, it is impossible to anticipate and warn against every possible combination of circumstances that may occur. No warning can take the place of good common sense and prudent driving practices.

Good common sense and prudent driving practices do more to prevent accidents and injury than all of the warnings and instructions combined. E-Z-GO strongly suggests that all users and maintenance personnel read this entire manual paying particular attention to the CAUTIONS, WARNINGS and DANGERS contained therein.

If you have any questions regarding this vehicle, contact your E-Z-GO dealer or write to the address on the back cover of this publication, Attention: Customer Care Department.

E-Z-GO reserves the right to make design changes without obligation to make these changes on units previously sold. The information contained in this manual is subject to change without notice.

E-Z-GO IS NOT LIABLE FOR ERRORS IN THIS MANUAL. E-Z-GO IS NOT LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES THAT RESULT FROM THE USE OF THE MATERIAL IN THIS MANUAL.

This vehicle conforms to the current applicable standard(s) for safety and performance requirements.

These vehicles are designed and manufactured for off-road use. They DO NOT conform to Federal Motor Vehicle Safety Standards of the United States of America (USA) and are not equipped for operation on public streets. Some communities may permit these vehicles to be operated on their streets on a limited basis and in accordance with local ordinances.

With electric powered vehicles, be sure that all electrical accessories are grounded directly to the battery (-) post. **Never use the chassis or body as a ground connection.**

Refer to GENERAL SPECIFICATIONS for vehicle seating capacity.

**Never modify the vehicle in any way that will alter the weight distribution of the vehicle, decrease its stability or increase the speed or extend the stopping distance beyond the factory specification. Such modifications can result in serious personal injury or death.**

Do not make any such modifications or changes. E-Z-GO prohibits and disclaims responsibility for all such modifications or alterations which would adversely affect the safety of the vehicle.

Vehicles that are capable of higher speeds must limit their speed to no more than the speed of other vehicles when used in a golf course environment. Additionally, speed should be further moderated by the environmental conditions, terrain and common sense.

Operation of the vehicle is limited to persons above the height of 59 inches (150 cm).

## GENERAL OPERATION

### ALWAYS:

- use the vehicle in a responsible manner and maintain the vehicle in safe operating condition
- read and observe all warnings and operation instruction labels affixed to the vehicle
- follow all safety rules established in the area where the vehicle is being operated
- Leave the vehicle when there is a risk of lightning
- reduce speed to compensate for poor terrain or conditions

# SAFETY

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

1

- apply service brake to control speed on steep grades
- maintain adequate distance between vehicles
- maintain adequate distance between vehicles
- reduce speed in wet areas
- use extreme caution when approaching sharp or blind turns
- use extreme caution when driving over loose terrain
- use extreme caution in areas where pedestrians are present

## MAINTENANCE

### ALWAYS:

- replace damaged or missing warning, caution or information labels
- maintain the vehicle in accordance with the manufacturer's periodic service schedule
- ensure that repairs are performed by trained and qualified personnel
- follow the manufacturer's maintenance procedures
- insulate any tools used within the battery area in order to prevent sparks or battery explosion
- check the polarity of each battery terminal and be sure to rewire the batteries correctly
- use specified replacement parts, NEVER use replacement parts of lesser quality
- use recommended tools
- determine that tools and procedures not specifically recommended by the manufacturer will not compromise the safety of personnel nor jeopardize the safe operation of the vehicle
- support the vehicle using wheel chocks and jack stands, NEVER get under a vehicle that is supported by a jack, lift the vehicle in accordance with the manufacturer's instructions
- maintain the vehicle in an area away from exposed flame or persons who are smoking
- be aware that a vehicle that is not performing as designed is a potential hazard and must not be operated
- test drive the vehicle after any repairs or maintenance in a safe area that is free of both vehicular and pedestrian traffic
- keep complete records of the maintenance history of the vehicle

The manufacturer cannot anticipate all situations, therefore people attempting to maintain or repair the vehicle must have the skill and experience to recognize and protect themselves from potential situations that could result in severe personal injury or death and damage to the vehicle. Use extreme caution and, if unsure as to the potential for injury, refer the repair or maintenance to a qualified mechanic.


## VENTILATION

Always store gasoline vehicles in a well ventilated area. Ventilation prevents gasoline fumes from accumulating.

Never fuel a vehicle in an area that is subject to flame or spark. Pay particular attention to natural gas or propane water heaters and furnaces.

Never work around or operate a vehicle in an environment that does not ventilate exhaust gases from the area. Carbon monoxide is a dangerous gas that can cause unconsciousness and is potentially lethal.


## LABELS AND PICTOGRAMS



35493G01



614058  
068



**⚠ WARNING**

**DO NOT TAMPER WITH OR ATTEMPT TO CHANGE THE ADJUSTMENT OF THE GOVERNOR. GOVERNOR TAMPERING CAN RESULT IN SERIOUS PERSONAL INJURY AND WILL VOID THE VEHICLE WARRANTY.**

608527

# SAFETY

Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.

1

1.



**WARNING**

2.



**READ MANUAL**

3.



**WARNING**  
USE CAUTION IN  
INCLEMENT WEATHER

4.




**WARNING**  
DO NOT OPERATE  
IF USING ALCOHOL  
OR DRUGS

5.



**MAXIMUM**  
CROSS HILL/RAMP  
ANGLE AS SPECIFIED

6.




**WARNING**  
MAXIMUM CROSS  
HILL/RAMP  
ANGLE AS  
SPECIFIED

7.




LOAD WITH  
HIGH CENTER  
OF GRAVITY  
COULD RESULT  
IN TIP OVER

8.




LOAD  
CENTER  
OF GRAVITY,  
MAXIMUM  
HEIGHT

9.



**WARNING**  
READ MANUAL  
FOR MAXIMUM  
LOAD BED  
CAPACITY.  
MAXIMUM RAMP/HILL

10.



**SECURE LOAD**  
AS FAR FORWARD  
AS POSSIBLE.  
MAXIMUM LOAD BED  
CAPACITY

11.




**DO NOT RIDE IN**  
LOAD BED

12.



**DANGER OF EXPLOSION**  
DO NOT FILL GAS CAN  
IN LOAD BED

13.



**WARNING**  
MAXIMUM LOAD  
& CENTER OF  
GRAVITY.  
KEEP LOAD  
AS FAR  
FORWARD AS  
POSSIBLE.  
DO NOT RIDE  
IN LOAD BED


14.



**KEEP HANDS &**  
**FINGERS AWAY**  
**FROM DUMP BED.**  
**DO NOT STAND**  
**BEHIND DUMP**  
**BED**

Ref Pic 1-1

Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.

15.  CLEAN UP GASOLINE SPILLS WITH WATER BEFORE STARTING ENGINE
16.  UNLEADED GASOLINE
17.  DO NOT SPILL FUEL ON A HOT ENGINE
18.  GROUND FUEL PUMP
19.  LOW OIL PRESSURE
20.  NEGATIVE GROUND BATTERY
21.  DO NOT CONNECT POSITIVE BATTERY TERMINAL TO GROUND
22.  SHORTING BATTERY TERMINALS MAY CAUSE EXPLOSION
23.  NO TAMPERING. KEEP HANDS OUT
24.  WARNING CORROSIVE
25.  WARNING EXPLOSIVE
26.  WARNING LETHAL VOLTAGE
27.  DO NOT EXPOSE TO FLAME
28.  DO NOT DISPOSE OF BATTERIES IN LANDFILL
29.  DO NOT DRIVE ON HIGHWAY
30.  WINDSHIELDS DO NOT PROVIDE PROTECTION FROM FLYING OBJECTS
31.  BATTERIES ARE HEAVY. USE CARE LIFTING
32.  USE INSULATED TOOLS
33.  WEAR EYE PROTECTION
34.  NO SMOKING
35.  HOT SURFACE

Ref Pic 1-2

# SAFETY

Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.

1

36.




OPERATE  
FROM  
DRIVERS SIDE  
ONLY

37.




KEEP ARMS  
AND LEGS  
WITHIN VEHICLE

38.




TO OPERATE VEHICLE IN FORWARD:  
\* TURN KEY TO ON  
\* MOVE DIRECTION SELECTOR TO  
FORWARD  
\* DEPRESS ACCELERATOR PEDAL  
AND ACCELERATE SMOOTHLY

39.




TO OPERATE VEHICLE IN REVERSE:  
\* TURN KEY TO ON  
\* MOVE DIRECTION SELECTOR TO  
REVERSE  
\* AN AUDIBLE DEVICE WILL SOUND  
\* DEPRESS ACCELERATOR PEDAL  
AND ACCELERATE SMOOTHLY

40.



TO LEAVE A GASOLINE POWERED  
VEHICLE IN PARK:  
\* APPLY PARKING BRAKE  
\* TURN KEY TO OFF  
\* MOVE DIRECTION SELECTOR TO  
FORWARD

41.



TO LEAVE AN ELECTRIC POWERED  
VEHICLE IN PARK:  
\* APPLY PARKING BRAKE  
\* TURN KEY TO OFF  
\* MOVE DIRECTION SELECTOR TO  
NEUTRAL

42.



KEEP CLEAR  
HAND OR  
FINGERS CAN  
BE TRAPPED

43.



ON  
POSITION

44.



OFF  
POSITION

45.



HEADLIGHTS

46.



UNLOCKED

47.



LOCKED

48.



DIFFERENTIAL  
LOCKED

49.



**WARNING**  
KEEP ENTIRE BODY  
INSIDE CAR

50.



**WARNING**  
POSSIBLE ELECTRIC  
ARC OR BATTERY  
EXPLOSION. WEAR  
EYE PROTECTION.

Ref Pic 1-3

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## Notes:

1

# SAFETY

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## 1 Notes:

# GENERAL SPECIFICATIONS

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

| TITLE                                                  | PAGE NO. |
|--------------------------------------------------------|----------|
| Vehicle Specifications .....                           | 2 - 3    |
| Vehicle Dimensions .....                               | 2 - 4    |
| Vehicle Incline Information and Turning Diameter ..... | 2 - 5    |

## GENERAL SPECIFICATIONS

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## Notes:

2

# GENERAL SPECIFICATIONS

Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.



A Textron Company

**MODEL: TERRAIN 250**  
**TYPE: GASOLINE POWERED TRUCK**  
**MODEL YEAR: 2012**  
**Part No.: 618855**



2

## PRODUCT SPECIFICATION

### CONFIGURATION HIGHLIGHTS

**Engine:** 13 hp (9.7 kW) Exceeds SAE J1940 Standard, 4 cycle, 24.5 ci (401 cc) single cylinder, air-cooled by Kawasaki

- **Valve Train:** Overhead valve
- **Lubrication:** Pressurized oil system, spin-on oil filter
- **Balancer:** Internal counter rotating balance shaft
- **Fuel System:** Fixed float bowl with remote pulse fuel pump
- **Ignition:** Electronic spark/magneto
- **Air Cleaner:** Replaceable dry cartridge

**Electrical:** Starter/Generator, solid-state regulator, 12 Volt maintenance free battery (425 CCA, 60 minute reserve)

**Drive Train:** Automatic, continuously variable transmission (CVT)

**Brakes:** Dual rear wheel mechanical self-adjusting drum brakes. Automatic single point park brake release with self-compensating system

**Transaxle:** Differential with helical gears, ground speed governor, forward/reverse

**Cargo Bed:** Roto-molded cross-linked polyethylene. Lifts for access to powertrain. Removable hinged multi-position tailgate requires no latch mechanism

## PRODUCT OVERVIEW

### Dimensions

|                              |                                            |
|------------------------------|--------------------------------------------|
| Overall Length               | 103.0 in (260.0 cm)                        |
| Overall Width                | 46.5 in (118.0 cm)                         |
| Overall Height (No Canopy)   | 49.0 in (124.0 cm) (Top of steering wheel) |
| Overall Height (With Canopy) | 79.5 in (186.0 cm)                         |
| Wheel Base                   | 65.5 in (166.0 cm)                         |
| Front Wheel Track            | 37.0 in (94.0 cm)                          |
| Rear Wheel Track             | 38.0 in (97.0 cm)                          |
| Gnd Clearance @ Differential | 4.3 in (15.0 cm)                           |
| Cargo Box Width (inside)     | 44.5 in (113.0 cm)                         |
| Cargo Box Length (inside)    | 30.5 in (77.0 cm)                          |
| Cargo Box Depth (inside)     | 7.5 in (19.0 cm)                           |
| Cargo Box Capacity           | 5.9 cu ft (0.17 m <sup>3</sup> )           |
| Cargo Box Material           | Roto-molded polyethylene                   |

### Vehicle Power

|                       |                                          |
|-----------------------|------------------------------------------|
| Power Source          | 4 Cycle 24.5 cu in (401 cc).             |
| Valve Train           | Single Cylinder OHV                      |
| Horsepower (kW)       | 13 hp (9.7 kW) Exceeds SAE J1940 Std.    |
| Electrical System     | Starter/Generator, Solid State Regulator |
| Batteries (Qty, Type) | One, 12 Volt Maintenance Free            |
| Key or Pedal Start    | Pedal                                    |
| Air Cleaner           | Replaceable Dry Cartridge                |
| Lubrication           | Pressurized Oil System                   |
| Oil Filter            | Spin-On                                  |
| Cooling System        | Air Cooled                               |
| Fuel Capacity         | 5.3 Gallons (20.0 L) tank                |
| Drive Train           | Continuously variable transmission (CVT) |
| Transaxle             | Differential with helical gears          |
| Gear Selection        | Forward - Reverse                        |
| Rear Axle Ratio       | 11.42:1 (Forward) 15.78:1 (Reverse)      |

### Performance

|                              |                                                                                                              |
|------------------------------|--------------------------------------------------------------------------------------------------------------|
| Seating Capacity             | 2 Persons                                                                                                    |
| Dry Weight                   | 810 lb (360 kg)                                                                                              |
| Curb Weight                  | 850 lb (385 kg)                                                                                              |
| Bed Load Capacity            | 400 lb (180 kg)                                                                                              |
| Vehicle load capacity        | 800 lb (360 kg)                                                                                              |
| Outside Clearance Circle     | 18.9 ft (5.8 m)                                                                                              |
| Intersecting Aisle Clearance | N/A                                                                                                          |
| Speed (Level Ground)         | Fwd - 15.0 mph $\pm$ 0.5 mph (24 kph $\pm$ 0.8 kph)<br>Rev - 12.3 mph $\pm$ 0.5 mph (19.8 kph $\pm$ 0.8 kph) |
| 400 lb (180 kg)              | 400 lb (180 kg)                                                                                              |

### Steering & Suspension

|                  |                                                       |
|------------------|-------------------------------------------------------|
| Steering         | Self-compensating rack and pinion                     |
| Front Suspension | Leaf springs with hydraulic shock absorbers           |
| Rear Suspension  | Leaf springs with hydraulic shock absorbers           |
| Service Brake    | Rear wheel mechanical self-adjusting drum             |
| Parking Brake    | Self-compensating, single point engagement            |
| Front Tires      | Trail Wolf 20 x 11 - 10 (4 Ply Rated) Uni-directional |
| Rear Tires       | Trail Wolf 20 x 11 - 10 (4 Ply Rated) Uni-directional |

### Body & Chassis

|                     |                                           |
|---------------------|-------------------------------------------|
| Frame               | Welded steel with DuraShield™ powder coat |
| Front Body & Finish | Injection molded TPO                      |
| Rear Body & Finish  | Steel. Base coat/clear coat               |
| Standard Color      | Black                                     |

### Noise & Vibration

|                |                                                                              |
|----------------|------------------------------------------------------------------------------|
| Noise          | Sound pressure; continued A-weighted equal to or less than 76 db(A)          |
| Vibration, WBV | Highest RMS value of weighted acceleration is less than 2.5 m/s <sup>2</sup> |
| Vibration, HAV | Highest RMS value of weighted acceleration is less than 2.5 m/s <sup>2</sup> |

The uncertainty of measurement is 0.54 m/s<sup>2</sup>  
Measurement methods were applied per the ISO 2631 and ISO 5349 standards under conditions of typical vehicle surfaces.

Some items shown may be optional equipment


Specifications are subject to change without notice

\* Field installed accessories may require installation charges

# GENERAL SPECIFICATIONS

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*


2




# GENERAL SPECIFICATIONS

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*


2



RECOMMENDED MAX SIDE TILT  
25% or 14° MAX



RECOMMENDED MAX RAMP GRADE  
25% or 14° MAX



## GENERAL SPECIFICATIONS

***Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.***

## Notes:

2

Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.

| TITLE                                  | PAGE NO. |
|----------------------------------------|----------|
| FEATURES.....                          | 3-3      |
| General Information .....              | 3-3      |
| Key Switch / Headlight Switch.....     | 3-4      |
| Low Oil Pressure Indicator Light ..... | 3-4      |
| Fuel Guage .....                       | 3-4      |
| Direction Selector.....                | 3-4      |
| Accelerator Pedal.....                 | 3-4      |
| Brake and Park Brake .....             | 3-4      |
| Horn .....                             | 3-5      |
| Front Seats.....                       | 3-5      |
| Hip Restraint - Front.....             | 3-5      |
| Brake Light/Turn Signal.....           | 3-5      |
| Glove Box.....                         | 3-5      |
| Cup Holder .....                       | 3-5      |
| Steering Wheel.....                    | 3-5      |
| Choke.....                             | 3-5      |
| Manual Lift Bed Operation .....        | 3-6      |

# INTRODUCTION

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## Notes:

# 3

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*


## FEATURES

### General Information

#### NOTICE

*If the vehicle is equipped with factory installed custom accessories, some accessories remain operational with the key switch in the 'OFF' position.*

3



# INTRODUCTION

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## 1. Key Switch / Headlight Switch

Located on the dash panel, this switch enables the basic electrical system of the vehicle to be turned on and off by turning the key. To prevent inadvertent operation of the vehicle when left unattended, the key should be turned to the 'OFF' position and removed.

## 2. Low Oil Pressure Indicator Light

3

A low oil pressure indicator light is located on the dash panel. The light illuminates when the oil pressure is low. Check oil level. If oil level is between ADD and FULL mark on dipstick, a mechanical problem exists within the engine and the vehicle **must not be driven**. Contact a local distributor or authorized branch

## 3. Fuel Gauge

The fuel gauge (if equipped) will either be located on the dash panel (electric) or directly on the fuel tank (mechanical).

## 4. Direction Selector



### CAUTION

*To reduce the possibility of component damage, the vehicle must be completely stopped before moving the direction selector.*

Located on the seat support panel, this lever permits the selection of either 'F' (forward) or 'R' (reverse). Vehicle should be left in 'F' when unattended.

## 5. Accelerator Pedal



### WARNING

*Unintentional movement of the accelerator pedal will release the park brake and may cause the vehicle to move which could result in severe injury or death.*

With the key switch 'ON', depressing the accelerator pedal starts the engine. When the pedal is released, the engine will stop. To stop the vehicle more quickly, depress the service brake.

If key switch is 'ON' and park brake is set, depressing the accelerator inadvertently will release the park brake and will cause the vehicle to move which could cause severe injury or death.

Depressing the accelerator pedal will release the park brake if it is engaged. This is a feature to assure the vehicle is not driven with the park brake engaged. Depressing the accelerator pedal is **not** the preferred method of releasing the park brake.

### NOTICE

*Depressing the **lower section of the brake pedal** is the preferred method of releasing the park brake to assure the longest service life of brake components.*

## 6. Brake and Park Brake

The brake pedal incorporates a park brake feature. To engage, push down on the upper section of the pedal until it locks in place. The park brake will release when the service brake pedal is depressed. Use the lower section of the brake pedal to operate the service brake system.

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## 7. Horn

The horn is operated by pushing the horn button located on the floor to the left of the brake pedal.

## Rear View Mirror

The rear view mirror is a two-position mirror manually adjusted for day and nighttime conditions. Sun Top kit is required to install rear view mirror.

## 8. Front Seats

The split bench front seat is designed for one occupant on each side of the center console.

## 9. Hip Restraint - Front

The front hip restraints are designed to help keep the occupants properly positioned in the event of sudden vehicle position changes.

## 10. Brake Light/Turn Signal

The combination brake light/turn signal assemblies are located on the rear fenders.

## 11. Glove Box

A passenger-side locking glove box is standard, driver-side is offered as an option. A separate key is used for the locking glove boxes.

## 12. Cup Holder

A cup holder is provided for convenience of both the driver and passenger.

## 13. Steering Wheel

The steering wheel located in front of the driver seat is used to steer the vehicle. The steering wheel is also installed with scorecard holder assembly.

## 14. Choke

The choke is used to aid cold starting . See COLD STARTING section for operating instructions.




## WARNING

*To prevent severe injury or death, rear seat passengers should hold on to both the hip restraints and the rear hand hold when the vehicle is in motion. Always be sure that all passengers are seated and holding on before operating vehicle.*

# INTRODUCTION

Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.

3



## 15. Manual Lift Bed Operation



## WARNING

*Exercise caution while operating the manual lift bed to ensure the bed is not released during lifting or lowering procedure. Severe injury could result if bed is released and traps fingers or other body parts.*

To raise the manual lift bed, pull back on the latch release handle immediately behind the driver seat. Raise the bed using the handle on the side of the bed.

To lower the manual lift bed, grasp the bed handle and lower the bed to the rest position. Be sure hands are not trapped by the bed.

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## Notes:

# INTRODUCTION

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## Notes:

# 3

# OPERATING PROCEDURES

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

| TITLE                             | PAGE NO. |
|-----------------------------------|----------|
| Serial Number Location .....      | 4-3      |
| Before Initial Use.....           | 4-4      |
| Operating the Vehicle .....       | 4-4      |
| Run-in.....                       | 4-5      |
| Cold Starting .....               | 4-6      |
| Starting and Driving.....         | 4-6      |
| Starting the Vehicle on Hill..... | 4-7      |
| Coasting .....                    | 4-7      |
| Fuel .....                        | 4-7      |
| Battery.....                      | 4-8      |
| SunTop and Windshield .....       | 4-8      |
| Towing a Trailer .....            | 4-9      |

# OPERATING PROCEDURES

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## Notes:

4


# OPERATING PROCEDURES

Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.

## Serial Number Location

Two serial number and manufacture date code plates are on the vehicle. One is placed on the body below the front, driver side of the seat. The other is located on the chassis between the seat back supports. To access it, raise the seat and lift up the flap on the access panel.

Design changes take place on an ongoing basis. In order to obtain correct components for the vehicle, the manufacture date code, serial number and vehicle model must be provided when ordering service parts.



**TEXTRON**  
GOLF, TURF & SPECIALTY PRODUCTS

Augusta Georgia, USA  
1 800 241-5855

MODEL

DATE CODE

SERIAL No.

Bar Code

Lb / kg W Batt  
Nom Power Hp / kw  
Label No.

Rated Capacity W/Operator lb/kg / System voltage V

Lb/kg W/O Batt / Max Batt lb/kg /

Max Draw bar lb/kg /

SERIAL No.

Bar Code

Serial Number & Location

# OPERATING PROCEDURES

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## BEFORE INITIAL USE

Read and follow the safety label on the instrument panel. Be sure you understand how to operate the vehicle and its equipment as well as how to use it safely. Maintaining good performance depends to a large extent on the operator.

Before a new vehicle is put into operation, the items shown in the **INITIAL SERVICE CHART** must be performed.

Vehicle battery must be fully charged before initial use.

Check for correct tire inflation. See GENERAL SPECIFICATIONS.

Check for oil or fuel leaks that could have developed in shipment from the factory.

4 Determine and record braking distance required to stop vehicle for future brake performance tests.

Remove the protective clear plastic, that protect the seat bottom and back rest during shipping, before placing the vehicle in service.

| ITEM    | SERVICE OPERATION                       |
|---------|-----------------------------------------|
| Battery | Charge battery                          |
| Seats   | Remove protective plastic covering      |
| Brakes  | Check operation and adjust if necessary |
|         | Establish acceptable stopping distance  |
| Tires   | Check air pressure (see SPECIFICATIONS) |
| Fuel    | Fill tank with correct fuel             |
| Engine  | Check oil level                         |

Ref Isc 16

**Initial Service Chart**

## OPERATING THE VEHICLE



### CAUTION

*Improper use of the vehicle or the lack of proper maintenance may result in damage or decreased performance. Read and understand the following warnings before attempting to operate the vehicle.*



### WARNING

*To reduce the possibility of severe injury or death resulting from loss of vehicle control, the following warnings must be observed:*

*When driving vehicle, consider the terrain, traffic conditions and the environmental factors which effect the terrain and the ability to control the vehicle.*

*Use extra care and reduced speed when driving on poor surfaces, such as loose dirt, wet grass, gravel, etc.*

*Stay in designated areas and avoid extremely rough terrain.*

*Maintain a safe speed when driving down hill. Use service brake to control speed when traveling*

# OPERATING PROCEDURES

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

*down an incline. A sudden stop or change of direction may result in loss of control.*

*Slow down before and during turns. All turns should be made at reduced speed.*

*Never drive vehicle up, down, or across an incline that exceeds 14° (25% grade).*

## WARNING

*To reduce the possibility of severe injury or death resulting from improper vehicle operation, the following warnings must be observed:*

*Refer to GENERAL SPECIFICATIONS for seating capacity.*

*Depressing accelerator pedal will release foot operated park brake and may cause inadvertent vehicle movement. Turn the key to the 'OFF' position whenever the vehicle is parked.*

*To prevent inadvertent movement when the vehicle is to be left unattended, engage the park brake, move direction selector to forward position, turn key to 'OFF' position and remove key.*

*Make sure that the direction selector is in correct position before attempting to start the vehicle.*

*Always bring the vehicle to a complete stop before shifting the direction selector.*

*Do not take vehicle out of 'gear' while in motion (coast).*

*Check the area behind the vehicle before operating in reverse.*


*All occupants must be seated. Keep entire body inside vehicle and hold on while vehicle is in motion.*

### Run-in

Check for oil or fuel leaks that could have developed in shipment from the factory. Avoid full throttle starts and rapid acceleration until the engine has achieved operating temperature.

All engines consume more oil than normal during the first hours of operation. As internal moving parts are run-in, oil consumption should gradually decrease until the rate of consumption stabilizes.

Check the oil level per the Periodic Service Schedule. Add oil if the level on the dipstick indicates that oil is in the add oil range.



Check Oil Level on DipStick

# OPERATING PROCEDURES

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*



## CAUTION

*Do not overfill engine. Too much oil may cause smoking or allow oil to enter the air filter enclosure.*


## NOTICE

*The oil dipstick/fill cap must be in place before operating the engine. Failure to install the dipstick/fill cap will result in oil becoming contaminated and/or being discharged into the engine compartment.*

4

Oil dipsticks are unique to this model vehicle. Do not interchange oil dipsticks between models.

The oil should be changed in accordance with the Periodic Service Schedule while the engine is warm. See SERVICE AND MAINTENANCE for checking oil level and changing oil procedures.



**Clean Entire Dipstick**

## Cold Starting

Starting a cold engine **may** require use of the choke. Depress the accelerator approximately 1" (2.5 cm) or until the starter just begins to operate. Pull the choke out if required. Accelerate slowly and push the choke in completely when the engine runs smoothly.



## CAUTION

*Do not allow the starter to operate continuously for more than 10 seconds. Allow 30 seconds between starting attempts. If the vehicle does not start on the third attempt, turn the key switch off, set the park brake and determine the cause of the problem.*

If the vehicle had been running and the engine does not start within 10 seconds, use the choke.

## Starting And Driving



## WARNING

*To reduce the possibility of roll-back which could result in severe injury or vehicle damage, do not release service brake until engine has started.*

To operate vehicle:

- Apply the service brake, place the key in the key switch and turn it to the 'ON' position.
- Move the direction selector to the direction desired.
- Release the park brake by depressing the service brake pedal until the park brake releases.
- Slowly depress the accelerator pedal to start the engine. Release service brake when engine starts.

# OPERATING PROCEDURES

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

- When the accelerator pedal is released, the ignition circuit is de-energized and the engine stops. To stop the vehicle more quickly, depress the **service brake pedal**

## NOTICE

*When the direction selector is in the reverse position, a warning signal will sound to indicate that the vehicle is ready to run in reverse.*

### Starting The Vehicle On A Hill

## WARNING

*To reduce the possibility of roll-back which could result in severe injury or vehicle damage, do not release service brake until engine has started.*

## CAUTION

*Do not hold vehicle on hill by using accelerator and engine. This will cause premature and excessive wear to drive train components.*

To reduce the possibility of permanent damage to the drive system, it is important to prevent excessive roll-back when starting the vehicle on a hill.

Place left foot on service brake and release the park brake. Depress accelerator with right foot and release the service brake by lifting left foot.

### Coasting

## WARNING

*To reduce the possibility of severe injury or death from coasting at above recommended speeds, limit speed with service brake.*

On steep hills, it is possible for the vehicle to coast at greater than normal speeds encountered on a flat surface. To reduce the possible loss of vehicle control and severe drivetrain damage, speeds should be limited to no more than the maximum governed speed on level ground (see GENERAL SPECIFICATIONS). Limit speed by applying service brake.

### Fuel

## WARNING

*To reduce the possibility of severe injury or death from improper fuel handling:*

*Do not smoke near the fuel tank.*

*Do not refuel near open flame or electrical items which could produce a spark.*

*Always handle gasoline in a well ventilated area.*

*Always wear eye protection to protect against splashed fuel and fuel vapors.*

*Always allow adequate space for the expansion of gasoline. Leave at least 1" (2.5 cm) space below bottom of filler neck.*

*Inspect fuel cap, tank and other components for leaks or deterioration that could cause a hazardous condition.*

# OPERATING PROCEDURES

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

The fuel tank is located under the seat on the passenger side of the vehicle. Fill the tank with fresh, clean, automotive grade gasoline. High altitude or heavy use/load applications may benefit from higher octane gasoline.


**Do not** use gasoline which contains Methanol.



## CAUTION

*Some fuels, called oxygenated or reformulated gasoline, are gasoline blended with alcohols or ethers. Excessive amounts of these blends can damage the fuel system or cause performance problems. If any undesirable operating symptoms occur, use gasoline with a lower percentage of alcohol or ether.*

**4** Use fresh regular grade unleaded fuel. Ethanol blend fuel upto 10% is permissible.



### Fueling

### Battery



## CAUTION

*Excessive use of accessories may drain the battery and leave insufficient reserve to start the vehicle.*

The vehicle uses a combination starter/generator to both start the engine and charge the battery. The engine will not idle; therefore, the battery cannot be charged while the vehicle is stopped. Do not operate accessory items (such as lights) excessively while the vehicle is stopped.

The generator is capable of supplying 35 amps; therefore, operation of all accessories could result in the discharge of the battery even though the engine is running and the generator operating. Discharging the battery is known as deep cycling. The battery is not a deep cycle model, but is a starting battery. Multiple deep cycling will result in the premature failure of the battery.

If the vehicle battery has become discharged, it must be charged using a 12 volt charger that is rated at 10 amps or less and in accordance with all instructions provided by the manufacturer of the charger.

### Sun Top And Windshield



## WARNING

*The sun top does not provide protection from roll over or falling objects.*

# OPERATING PROCEDURES

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

*The windshield does not provide protection from tree limbs or flying objects.*



## CAUTION

*To prevent damage to the vehicle, do not hold on to sun top struts and stand on body panels.*

The sun top and windshield provide some protection from the elements; however, they will not keep the operator and passenger dry in a downpour. This vehicle is not equipped with seat belts and the sun top has not been designed to provide roll over protection. In addition, the sun top does not protect against falling objects nor does the windshield protect against flying objects and tree limbs. Keep arms and legs inside of vehicle while it is moving.

4

## Towing A Trailer



## CAUTION

The vehicle is equipped with a receiver that can be fitted with a standard 1 7/8" ball. The trailer and its load must not exceed 500 lbs (227 kg) and no more than 50 lbs (23 kg) tongue weight may be attached to the hitch. Remember that the overall capacity of the vehicle, operator, passenger, contents of load bed and accessories must be reduced to compensate for the trailer and load.

The range of motion of the trailer is limited by the ball and hitch. The trailer should not be used on rough trails or over objects such as logs, large rocks, holes, etc.

Never install baskets or extensions using the hitch receivers (front or rear). Such items will change the performance characteristics of vehicle and result in unsafe handling, possible roll over or vehicle damage.

# OPERATING PROCEDURES

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## Notes:

4

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

| <b>TITLE</b>                                           | <b>PAGE NO.</b> |
|--------------------------------------------------------|-----------------|
| <b>Vehicle Cleaning And Care.....</b>                  | <b>5-4</b>      |
| Vehicle Cleaning .....                                 | 5-4             |
| <b>Repair.....</b>                                     | <b>5-5</b>      |
| Lifting the Vehicle.....                               | 5-5             |
| <b>Wheels And Tires .....</b>                          | <b>5-6</b>      |
| Tire Repair .....                                      | 5-6             |
| Wheel Installation.....                                | 5-7             |
| Unidirectional Tires .....                             | 5-7             |
| <b>Light Bulb Replacement .....</b>                    | <b>5-8</b>      |
| <b>Fuse Replacement .....</b>                          | <b>5-8</b>      |
| <b>Vehicle With A Discharged Battery.....</b>          | <b>5-8</b>      |
| <b>Transporting Vehicle .....</b>                      | <b>5-9</b>      |
| Towing.....                                            | 5-9             |
| Neutral Lock.....                                      | 5-9             |
| Hauling .....                                          | 5-9             |
| <b>Service And Maintenance.....</b>                    | <b>5-10</b>     |
| <b>Routine Maintenance .....</b>                       | <b>5-11</b>     |
| Tire Inspection.....                                   | 5-11            |
| Rear Axle .....                                        | 5-11            |
| <b>Four Cycle Engine.....</b>                          | <b>5-11</b>     |
| Engine Specifications.....                             | 5-11            |
| Engine Description .....                               | 5-11            |
| Checking The oil Level.....                            | 5-11            |
| Changing the Oil .....                                 | 5-12            |
| <b>Starter Generator Belt Tension .....</b>            | <b>5-15</b>     |
| Adjusting the Belt .....                               | 5-15            |
| <b>Battery Cleaning.....</b>                           | <b>5-16</b>     |
| <b>Brakes .....</b>                                    | <b>5-17</b>     |
| <b>Periodic Brake Test For Mechanical Brakes .....</b> | <b>5-17</b>     |
| <b>Air Intake and Cooling Fins.....</b>                | <b>5-18</b>     |
| <b>Rear Axle .....</b>                                 | <b>5-18</b>     |
| Checking the Lubrican Level.....                       | 5-19            |
| <b>Air Cleaner Inspection and Replacement.....</b>     | <b>5-19</b>     |
| Cleaning the Air Filter Element .....                  | 5-19            |

# MAINTENANCE

**Lubrication..... 5-20**

**Spark Plugs..... 5-20**

**Prolonged Storage ..... 5-21**

**Periodic Service Schedule..... 5-22**

**Capacities and replacement Parts ..... 5-24**

**Hardware ..... 5-24**

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## Notes:

# MAINTENANCE

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## Vehicle Cleaning And Care

### Vehicle Cleaning

#### **WARNING**

*To reduce the possibility of severe injury or vehicle damage, read and understand all instructions supplied by manufacturer of pressure washer.*

#### **CAUTION**

**5** *When pressure washing exterior of vehicle, do not use pressure in excess of 700 psi. To reduce the possibility of cosmetic damage, do not use any abrasive or reactive solvents to clean plastic parts.*

It is important that proper techniques and cleaning materials be used. Using excessive water pressure may cause severe injury to operator or bystander, damage to seals, plastics, seat material, body finish or electrical system. Do not use pressure in excess of 700 psi to wash exterior of vehicle.

Clean windshield with lots of water and a clean cloth. Minor scratches may be removed using a commercial plastic polish or Plexus® plastic cleaner available from the service parts department.

Normal cleaning of vinyl seats and plastic or rubber trim requires the use of a mild soap solution applied with a sponge or soft brush and wipe with a damp cloth.

Removal of oil, tar, asphalt, shoe polish, etc. will require the use of a commercially available vinyl/rubber cleaner.

The painted surfaces of the vehicle provide attractive appearance and durable protection. Frequent washing with lukewarm or cold water and mild detergent is required to preserve the painted surfaces.

Occasional cleaning and waxing with non-abrasive products designed for 'clear coat' automotive finishes will enhance the appearance and durability of the painted surfaces.

Corrosive materials used as fertilizers or for dust control can collect on the underbody of the vehicle. These materials will cause corrosion of underbody parts unless flushed occasionally with plain water. Thoroughly clean any areas where mud or other debris can collect. Sediment packed in closed areas should be loosened to ease its removal, taking care not to chip or otherwise damage paint.

Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.

Repair

Some servicing operations may require the front wheels, the rear wheels, or the entire vehicle to be raised.

 **WARNING**

- To reduce the possibility of severe injury or death from a vehicle falling from a jack:
  - Be sure the vehicle is on a firm and level surface.
  - Never get under a vehicle while it is supported by a jack.
  - Use jack stands and test the stability of the vehicle on the stands.
  - Always place chocks in front and behind the wheels not being raised.
  - Use extreme care since the vehicle is extremely unstable during the lifting process.

5

 **CAUTION**

When lifting the vehicle, position the jacks and jack stands at the areas indicated only.

Lifting the Vehicle

| Tool List          | Qty. | Tool List         | Qty. |
|--------------------|------|-------------------|------|
| Floor jack .....   | 1    | Jack stands ..... | 4    |
| Wheel Chocks ..... | 4    |                   |      |

Remove payload from vehicle before lifting. No person(s) should be in or on the vehicle while lifting.

To raise the entire vehicle, install chocks in front and behind each front wheel. Center the jack under the rear frame crossmember. Raise the vehicle enough to place a jack stand under the outer ends of the rear axle.


Lower the jack and test the stability of the vehicle on the two jack stands.

Place the jack at the center of the front axle. Raise the vehicle enough to place jack stands under the frame crossmember as indicated.

Lower the jack and test the stability of the vehicle on all four jack stands.


If only the front or rear of the vehicle is to be raised, place the chocks in front and behind each wheel not being raised to stabilize the vehicle.

Lower the vehicle by reversing the lifting sequence.



# MAINTENANCE

Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.



5

## Wheels And Tires

### **WARNING**

*A tire explosion can cause severe injury or death. Never exceed the inflation pressure rating on the tire sidewall.*

*To reduce the possibility of tire explosion, pressurize tire with small amounts of air applied intermittently to seat beads. Due to the low volume of the small tires, overinflation can occur in seconds. Never exceed the tire manufacturer's recommendation when seating a bead. Protect face and eyes from escaping air when removing a valve core.*

*To reduce the possibility of severe injury caused by a broken socket when removing wheels, use only sockets designed for impact wrench use.*

*DO NOT use low inflation tires on any E-Z-GO vehicle. DO NOT use any tire which has a recommended inflation pressure less than the inflation pressure recommended in the owner's guide.*

*Use caution when inflating tires. Overinflation could cause the tire to separate from the wheel or cause the tire to explode, either of which could cause severe injury.*

### Tire Repair

| Tool List              | Qty. | Tool List                    | Qty. |
|------------------------|------|------------------------------|------|
| Lug wrench, 3/4" ..... | 1    | Impact socket, 3/4" .....    | 1    |
| Impact wrench .....    | 1    | Torque wrench, ft. lbs. .... | 1    |

Use caution when inflating tires. Due to the low volume of the small tires, overinflation can occur in seconds. Overinflation could cause the tire to separate from the wheel or cause the tire to explode.

Tire inflation should be determined by the condition of the terrain. See GENERAL SPECIFICATIONS section for recommended tire inflation pressure. For outdoor applications with major use on grassy areas, the following should be considered. On hard turf, it is desirable to have a slightly higher inflation pressure. On very soft turf, a lower pressure reduces the possibility of tires cutting into the turf. For vehicles being used on paved or hard surfaces, tire inflation pressure should be in the higher allowable range, but under no condition should inflation pressure be higher than recommended on tire sidewall. All four tires should have the same pressure for optimum handling characteristics. Be sure to install the valve stem dust cap after checking or inflating.

The vehicle is fitted with low pressure tubeless tires mounted on one piece rims; therefore, the most cost effective way to repair a puncture in the tread is to use a commercial tire plug.

Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.

## NOTICE

Tire plug tools and plugs are available at most automotive parts outlets and have the advantage of not requiring the tire be removed from the wheel.

If the tire is flat, remove the wheel and inflate the tire to the maximum recommended pressure for the tire. Immerse the tire in water to locate the leak and mark with chalk. Insert tire plug in accordance with manufacturer's instructions.

## WARNING

To reduce the possibility of severe injury, be sure the mounting/demounting machine is anchored to floor. Wear OSHA approved safety equipment when mounting/demounting tires.

If the tire is to be removed or mounted, the tire changing machine manufacturer's recommendations must be followed in order to reduce possibility of severe injury.

### Wheel Installation


## CAUTION

To reduce the possibility of component damage, do not tighten lug nuts to more than 85 ft. lbs. (115 Nm) torque.

## NOTICE



It is important to follow the 'cross sequence' pattern when installing lug nuts. This will assure even seating of the wheel against the hub.

With the valve stem to the outside, mount the wheel onto the hub with lug nuts. Finger tighten the lug nuts (1) in a 'cross sequence' pattern. Tighten the lug nuts to 50 to 85 ft. lbs. (68 to 115 Nm) torque in 20 ft. lbs. (27 Nm) increments following the 'cross sequence' pattern.



### Unidirectional Tires

Some vehicles may be fitted with unidirectional tires. These tires may be identified by a directional arrow on the sidewall. Be sure to position the wheel on hub correctly with arrow indicating direction of rotation when moving forward.



# MAINTENANCE


*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## Light Bulb Replacement



*To reduce the possibility of premature bulb failure, do not touch new bulbs with bare fingers. Use clean, dry tissue or paper towel to handle the glass portion of the bulb.*


For vehicles equipped with lights mounted in the cowl, locate bulb socket on backside of light and turn bulb socket a quarter turn counterclockwise to unlock and pull out bulb and socket. Insert new bulb and rotate socket a quarter turn clockwise to secure.



5

Similarly replace the turn signal light bulb, locate bulb socket on backside of light bar and turn bulb socket a quarter turn counterclockwise to unlock and pull out bulb and socket. Insert new bulb and rotate socket a quarter turn clockwise to secure..

To replace the tail and brake light bulb, roll the rubber bezel from around the edge of the taillight and remove lens. Install replacement bulb and replace lens.



## Fuse Replacement

To replace fuses, locate the fuse block under the driver side seat. Pull out old fuse and replace with a new automotive type fuse. Headlight and taillight bulbs and fuses are available from a local Distributor, an authorized Branch or the Service Parts Department.

## Vehicle With A Discharged Battery



*To reduce the possibility of severe injury or death from inadvertent motion, do not attempt to 'jump start' a vehicle.*

The vehicle is equipped with a starter/generator and does not idle. When starting the engine, the starter/generator functions as a starter and with the engine running, it functions as a generator.

With the short running times associated with this kind of vehicle, the generator is more than adequate to maintain the battery charge level. The generator is not designed to charge a discharged battery.

When engine starts, the clutches engage and cause vehicle to move making 'jump starting' both dangerous and impractical.

If the vehicle battery has become discharged, it must be charged using a 12 volt charger that is rated at 10 amps or less. Read and understand all instructions provided by the manufacturer of the charger.

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## Transporting Vehicle

### Towing



# WARNING

*This vehicle is not designed to be towed*


It is recommended that the vehicle be moved by placing the entire vehicle on a trailer, flatbed truck or other suitable transport.

### Neutral Lock

To prevent the driven clutch from turning the rear wheels during service operations, a neutral lock is located on the direction selector

To operate:

Turn key switch to 'OFF' and lift seat. Pull out and rotate the neutral lock pin handle so that the pointed portion of the handle is to the side of the direction selector cam. Move direction selector towards the area between 'F' and 'R'. During that motion the pin will snap into the hole in the direction selector mounting bracket preventing any movement.



When in this position, the direction selector remains locked in the neutral position. To unlock the direction selector, pull the neutral lock pin handle out and rotate until the pointed portion of the handle fits into the hole in the direction selector cam.

### Hauling



# WARNING

*To reduce the possibility of severe injury or death while transporting the vehicle:*

*Secure the vehicle and contents.*

*Never ride on the vehicle being transported.*

*Always remove the windshield before transporting.*

If the vehicle is to be transported at highway speeds, the sun top must be removed and the seat bottom secured. When transporting vehicle below highway speeds, check for tightness of hardware and cracks in sun top at mounting points. Always remove windshield when transporting. Always check that the vehicle and contents are adequately

# MAINTENANCE

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

secured before transporting. The rated capacity of the trailer or truck must exceed the weight of the vehicle (see GENERAL SPECIFICATIONS for vehicle weight) and load plus 1000 lbs. (454 kg). Secure the vehicle using ratchet tie downs.

## Service And Maintenance

### **WARNING**

*To reduce the possibility of severe injury or death from improper servicing techniques:*

*DO NOT attempt any type of servicing operations before reading all notes, cautions and warnings in this manual.*

*Any servicing requiring adjustments to be made to the powertrain while the motor is running must be made with both drive wheels raised and vehicle properly supported on jack stands.*

*To reduce the possibility of motor damage, never operate vehicle at full throttle for more than 4 - 5 seconds while vehicle is in a 'no load' condition.*

*Reduce the possibility of accidental starting by disconnecting battery at negative terminal before servicing.*



*Wear eye protection when working on the vehicle. Use extra care when working around batteries, or using solvents or compressed air.*

*To reduce the possibility of causing an electrical arc, which could result in a battery explosion, turn off all electrical loads from the battery before removing battery wires.*



*Wrap wrenches with vinyl tape to reduce the possibility of a dropped wrench 'shorting out' a battery, which could result in an explosion.*

*The electrolyte in a battery is an acid solution which can cause severe burns to the skin and eyes. Treat all electrolyte spills to the body and eyes with extended flushing with clear water. Contact a physician immediately.*

*Any electrolyte spills should be neutralized with a solution of 2 teaspoons (10 ml) sodium bicarbonate (baking soda) dissolved in 1 quart (1 liters) of water and flushed with water.*

*Aerosol containers of battery terminal protectant must be used with extreme care. Insulate metal container to reduce the possibility of can contacting battery terminals which could result in an explosion.*

It is in the best interest of both vehicle owner and service technician to carefully follow the procedures recommended in this manual. Preventative maintenance, applied at recommended intervals, is the best guarantee for keeping the vehicle both dependable and economical.

This vehicle will give years of satisfactory service, providing it receives regular maintenance. Refer to the Periodic Service Schedule for appropriate service intervals.

Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.

Routine Maintenance



To prolong vehicle life, some maintenance items must be serviced more frequently on vehicles used under severe driving conditions such as extreme temperatures, extreme dust/debris conditions, or frequent use with maximum load.

To access the powertrain for routine maintenance, lift or remove the seat and remove the rear access panel. For major repair, refer to the appropriate Technician's Repair and Service Manual.  
Some service procedures may require the vehicle to be lifted. Refer to LIFTING THE VEHICLE for proper lifting procedure and safety information.

Tire Inspection

Tire condition should be inspected per the Periodic Service Schedule. Inflation pressures should be checked when the tires are cool. Be sure to install the valve dust cap after checking or inflating.

Rear Axle

The only maintenance required for the first five years is the periodic inspection of the rear axle for lubricant leakage. Unless leakage is evident, the lubricant need only be replaced after five years. Refer to the Service and Repair Manual for the fluid replacement procedure.

Four Cycle Engine

Engine Specifications

|                           |                                 |
|---------------------------|---------------------------------|
| Engine model .....        | FJ400D                          |
| Type .....                | Four cycle, OHV                 |
| Number of cylinders ..... | 1                               |
| Displacement .....        | 401 cc                          |
| Rated horsepower.....     | 13 hp                           |
| Spark plug type .....     | NGK BPR2ES                      |
| Spark plug gap .....      | .028" - .031" (.70 - .80 mm)    |
| Cooling .....             | Forced air cooled               |
| Oil Filter .....          | Cartridge type full flow filter |
| Oil Pump .....            | Positive displacement pump      |

Engine Description

The engine is an air cooled, 4-stroke, OHV, single cylinder gasoline engine. It incorporates a pressure fed lubrication positive displacement oil pump with a cartridge type full flow oil filter and a counter rotating balance shaft.

Checking The Oil Level




Do not overfill engine. Too much oil may cause engine to smoke or cause spark plug fouling.  
Do not overfill engine. Too much oil may cause smoking or allow oil to enter the air filter enclosure.  
The oil should be checked with the engine warm. The vehicle should be on a level surface with the parking (PARK) brake engaged. Allow adequate time for oil to drain into the crankcase before checking.

# MAINTENANCE


*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

Remove the dipstick and wipe off the entire area with a lint free cloth.



5

Insert the dipstick **fully** into the dipstick hole and remove. Examine the level of the oil on the dipstick.



The engine can be operated safely as long as oil is within the safe operating range as indicated on the dip stick. **Do not operate vehicle if oil level is below the safe area indicated on the dipstick.**

Oil should be added to bring the level into the safe operating range. Remember that oil expands as it gets hot, **Do not overfill**. Check that the oil cap is firmly in place.

## NOTICE

*When adding oil between oil changes, do not mix brands and viscosity grades of oil*

The oil dipstick/fill cap must be in place before operating the engine. Failure to install the dipstick/fill cap will result in oil becoming contaminated and/or oil being discharged into the engine compartment.

## Changing the Oil


### Tool List

|                                 | Qty. |
|---------------------------------|------|
| Socket, 3/8" drive .....        | 1    |
| Ratchet, 3/8" drive .....       | 1    |
| Extension, 3/8" drive, 8" ..... | 1    |
| Oil drain pan .....             | 1    |
| Wrench, 3/4" .....              | 1    |

For maximum performance and longevity, the engine oil should be replaced after the first 8 hours of operation. After the initial oil change, it should be changed every 125 hours of operation or semi-annually, whichever comes first.

The selection of oil is dependent upon the service that the vehicle will perform. Most vehicles require 10W-30 oil, whereas vehicles used at capacity or near capacity load applications will utilize 10W-40 oil after a break-in period of 100 hours.

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*



## NOTICE


*If vehicle is to be stored over winter months, it can be stored with old oil left in engine. The oil should be changed as part of spring maintenance. This will remove any moisture that has accumulated during storage.*

## WARNING


*Be aware that engine fluids may be hot and contact to the skin may cause severe burns. Wear rubber gloves to protect skin from exposure to the old oil and de greaser.*

The oil should be changed with engine warm. Park vehicle on a level surface, engage parking brake and remove key. Place a drain pan under engine. Wipe top of the engine clean with a cloth. Remove the oil fill cap.

Oil Fill Cap




Clean the area around filter. Using a filter wrench, strap wrench or other suitable wrench, remove the filter (B) from the engine and allow the oil to drain. The 'O' rings may remain on engine (A) or filter (B)



# MAINTENANCE

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*


Inspect the filter. Make sure the 'O' ring is not left on the engine surface.



## WARNING

*Be careful of hot oil when drained. It may be hot enough to burn you severely*

Drain the oil by removing the drain plug found at the rear of the engine base. Remove using a 3/4" wrench. At the first oil change, **small** metal chips and lint may be found. This is normal, resulting from the break-in period. Inspect the filter at every oil change. The presence of large metal chips could indicate possible damage to the engine.



Wipe the area around the drain plug mount with a lint free cloth and inspect the drain plug (A) for damage; replace if necessary. Replace the "O"-ring (B) with a new one and tighten to 61 in. lbs. (7.0 Nm) torque. Apply engine oil to the oil filter seal and install oil filter onto the engine until the seal contacts mounting surface of the engine. Then turn the filter 2/3 to 3/4 rotations by HAND(S). Pour in the specified type and amount of oil See "Capacity and Replacement Parts" chart on page 55.

Oil capacity is 1 1/3 quarts (1.3 liters). Add slightly less than 1 1/3 quarts (1.3 liters) to allow for possible residual oil left in engine. The oil must be high quality oil that meets or exceeds API SF, SG, CC standards. Check oil level on dipstick. Oil should be slightly below 'H' to allow for expansion. If necessary, continue to add oil slowly and allow time for oil to flow down into engine. Check oil level on dipstick. **Do not overfill.**




## CAUTION

*Do not overfill engine. Too much oil may cause smoking or allow oil to enter the air filter enclosure.*

## NOTICE

*Both the oil dipstick and fill cap must be in place before operating the engine. Failure to install the dipstick and fill cap will result in oil being discharged into the engine compartment*



Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.

As a final check, check the oil level again with the vehicle on level ground. Like all liquids, oil increases in volume when warm. The full 'H' mark on the dipstick is calibrated for an engine at operating temperature. When the engine is cold, the oil will be below the full mark. The engine can be operated safely as long as the oil is within the safe operating range as indicated on the dipstick. **Do not operate vehicle if oil level is below the safe area indicated on the dipstick.**

Starter/generator Belt Tension

| Tool List                     | Qty. |
|-------------------------------|------|
| Belt tension gauge .....      | 1    |
| Wrench, 3/4" .....            | 1    |
| Wrench, 9/16" .....           | 2    |
| Ratchet, 3/8" drive.....      | 1    |
| Socket, 3/4", 3/8" drive..... | 1    |

The starter/generator belt tension should be checked after the first 15 - 20 hours and set to 75 - 80 lbs. (34 - 36 kg).




At no time during installation of belt, should the belt tension exceed 160 lbs (73 kg).




At the time of installation, the belt must not be rolled over the installed edges of the starter/generator or drive clutch pulleys. Excessive stretch in belt may cause cord failure.



A loose belt can cause audible vibration and squeal.



Tighten a **new** starter/generator belt to 110 - 130 lbs. (50 - 59 kg) tension when a gauge is applied half way between the two pulleys.



A **new** belt may be checked manually. A maximum deflection of 3/8" (10 mm) is acceptable. Tighten an **existing** belt to 75 - 80 lbs. (34 - 36 kg) tension using the same technique and inspect for cracking or wear. A maximum deflection of 1/2" (13 mm) is acceptable.

# MAINTENANCE

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## Adjusting the Belt

Loosen the starter/generator pivot bolt. While holding the lower adjusting nut with a wrench, loosen the upper jam nut with another wrench. Move the lower nut up or down the adjustment bolt until proper belt tension is achieved. Hold the lower nut in place and tighten the upper jam nut against it.

Tighten the starter/generator pivot bolt.



5

## Battery Cleaning



### CAUTION

*To reduce the possibility of damage to vehicle or floor, neutralize acid before rinsing battery.*

*To reduce the possibility of damage to electrical components while cleaning, do not use a pressure washer.*

Cleaning should take place per the Periodic Service Schedule.

When cleaning the outside of the battery and terminals, first spray with a solution of sodium bicarbonate (baking soda) and water to neutralize any acid deposits before rinsing with clear water.

Use of a water hose without first neutralizing any acid, will move acid from the top of the battery to another area of the vehicle or storage facility where it will attack the metal structure or the concrete/asphalt floor. Additionally, a residue will be left on the battery which is conductive and will contribute to the discharge of the battery.




### WARNING

*To reduce the possibility of battery explosion that could result in severe injury or death, do not use metallic spray wand to clean battery and keep all smoking materials, open flame or sparks away from the battery.*

The correct cleaning technique is to spray the top and sides of the battery with a solution of sodium bicarbonate (baking soda) and water. This solution is best applied with a **plastic spray bottle**. The solution should consist of the 2 teaspoons (10 ml) of sodium bicarbonate (baking soda) and 1 quart (1 liter) clear water as shown. In addition to the battery, special attention should be paid to metal components adjacent to the battery which should also be sprayed with the sodium bicarbonate (baking soda) solution.

Allow the solution to sit for at least three minutes; use a soft bristle brush or cloth to wipe the tops of the battery to remove any residue that could contribute to the self discharge of the battery. Rinse the entire area with low pressure clear water. Do not use a pressure washer.



*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## BRAKES

### WARNING

*To reduce the possibility of severe injury or death, always evaluate pedal travel before operating a vehicle to verify some braking function is present.*


*All driving brake tests must be done in a safe location with regard for the safety of all personnel.*

### NOTICE

*Over time, a subtle loss of performance may take place; therefore, it is important to establish the standard with a new vehicle.*

The Periodic Brake Performance Test should be performed regularly as an evaluation of braking system performance. It is useful as a method of identifying subtle loss of performance over time.

### Periodic Brake Test For Mechanical Brakes



The purpose of this test is to compare the braking performance of the vehicle to the braking performance of new or 'known to be good' vehicles or to an established acceptable stopping distance. Actual stopping distances will be influenced by weather conditions, terrain, road surface condition, actual vehicle weight (accessories installed) and vehicle speed. No specific braking distance can be reliably specified. The test is conducted by latching the park brake to eliminate different pedal pressures and to include the affects of linkage mis-adjustment.

Establish the acceptable stopping distance by testing a new or 'known to be good' vehicle and recording the stopping location or stopping distance. For fleets of vehicles, several vehicles should be tested when new and the range of stopping locations or distances recorded.

### NOTICE

*Over time, a subtle loss of performance may take place; therefore, it is important to establish the standard with a new vehicle.*

Drive the vehicle at maximum speed on a flat, dry, clean, paved surface. Quickly depress the brake pedal to latch the parking brake at the line or marker in the test area and remove foot from pedal. The vehicle should stop aggressively. The wheel brakes may or may not lock. Observe the vehicle stopping location or measure the vehicle stopping

# MAINTENANCE

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

distance from the point at which the brakes were latched. The vehicle should stop within the 'normal' range of stopping distances. If the vehicle stops more than 4 ft. (1.2 m) beyond the acceptable stopping distance or pulls to one side, the vehicle has failed the test and should be tested again.


If the vehicle fails the second test, it should **immediately** be removed from service. The vehicle **must** be inspected by a qualified mechanic who should refer to the TROUBLESHOOTING section in the Technician's Repair and Service Manual.

## Air Intake and Cooling Fins

### WARNING

5 To prevent possible burns, engine parts should be kept clean to reduce risk of overheating and ignition of accumulated debris. After every off road use, allow to cool and then check for a build up of dirt and debris in the air intake and cooling fins. Dirt and debris may clog the engine's air cooling system. Clean areas shown to prevent engine damage. Keep linkages, springs and controls clean. Keep area around muffler free of any combustible material.

At least once a year, (or more often under adverse conditions) the cooling system should be cleaned. Cleaning will assure an adequate supply of air to the cooling fins. Compressed air may be used for routine cooling system maintenance.



## Rear Axle

The rear axle is provided with a lubricant level check plug located on the driver side at the rear of the housing. Unless leakage of rear axle lubricant is evident, an annual lubricant check is sufficient.

## Checking the Lubricant Level

### Tool List


|                                | Qty. |
|--------------------------------|------|
| Socket, 13 mm, 3/8" drive..... | 1    |
| Ratchet, 3/8" drive .....      | 1    |
| Funnel.....                    | 1    |

### NOTICE

*For vehicles with LSD axle, add 2 ounces of friction modifier during refill.*

Clean the area around the check and fill plugs. Remove the check plug. The correct lubricant level is **just** below the bottom of the threaded hole. If lubricant is to be added, remove the fill plug and add lubricant using a funnel. Add lubricant slowly until lubricant starts to seep from the check plug hole. Install the check plug and the fill plug. In the event that the lubricant is to be replaced, a drain plug is provided at the bottom of the differential housing.

Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.



5

## Air Cleaner Inspection And Replacement


The air cleaner unit on the vehicle is a dry unit. **Do not** use oil on the filter element or any part of the unit. To aid installation and sealing, petroleum jelly may be applied to back side of cover tabs and each side of filter seal.

## Cleaning the Air Filter Element

### CAUTION

*Do not use compressed air to clean the air filter; doing so will damage the filter which may result in damage to the engine.*

The air cleaner element is accessible by unsnapping the clips on the air canister and removing the cover and air filter element. Clean inside of cover, canister and dust collector. Install the element and cover the same way they were removed. Be sure the positioning arrow on cover is pointing upward and all clips are fastened securely.



Ref Air 2

If the element is in acceptable condition, loose dirt may be removed by tapping the filter lightly. Do not use oil on the filter element or any part of the unit.

# MAINTENANCE

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## LUBRICATION




### CAUTION

*Do not use more than three (3) pumps of grease in any grease fitting at any one time. Excess grease may cause grease seals to fail or grease migration into areas that could damage components.*

Putting more than three pumps of grease in a grease fitting could damage grease seals and cause premature bearing failure.

Lubrication Points



View from Underside of Vehicle

## SPARK PLUGS

### Tool List

|                                             | Qty. |
|---------------------------------------------|------|
| Spark plug socket, 13/16", 1/2" drive ..... | 1    |
| Ratchet, 1/2" drive .....                   | 1    |
| Plug gauge, wire type .....                 | 1    |
| Anti-seize compound .....                   | AR   |
| Torque wrench, 1/2" drive, ft. lbs. ....    | 1    |




### CAUTION

*Use care not to over-tighten the plug. Over-tightening can cause damage to the aluminum cylinder head threads. Remove and inspect the spark plug at intervals indicated in the Periodic Service Schedule. Spark plug should be properly gapped. Tighten to 16 ft. lbs. (22 Nm) torque*

Remove and inspect the spark plug at intervals indicated in the Periodic Service Schedule. Spark plug should be properly gapped. Tighten to 16 ft. lbs. (22 Nm) torque.

Fouled spark plug is indicated by a wet, black appearance. This could be caused by a dirty air filter element or other restrictions in the air intake system. Incorrectly adjusted valves, spark plug wire which are in poor condition or poor quality fuel could also contribute to the problem.



Ref Spg 15

Gapping the Spark plug

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## PROLONGED STORAGE

### **WARNING**

*To reduce the possibility of severe injury or death resulting from a possible explosion:*

*Do not handle fuel in an area that is not adequately ventilated. Do not smoke near the fuel tank or refuel near open flame or electrical items which could produce a spark.*

*Store vehicle in a clean, dry area. Do not store in same area as a stove, furnace, water heater, or other appliance that uses a pilot light or has a device that can create a spark.*


*When refueling, inspect the fuel cap for leaks or breaks that could result in fuel spillage.*

*Always wear safety glasses while refueling to prevent possible eye injury from gasoline or gasoline vapor.*

*Keep hands, clothing and jewelry away from moving parts. Use care not to contact hot objects. Raise the rear of the vehicle and support on jack stands before attempting to run the engine.*

Preparing the engine for a prolonged storage period (30 days or more) calls for a few simple steps to prevent a build up of varnish and gum in the carburetor and corrosion in the engine.

- Turn the Key Switch to OFF position, and leave the Forward/Reverse switch in the NEUTRAL position during storage.
- Perform all required routine maintenance per the Periodic Service Schedule.
- Properly inflate the tires to recommended pressure (psi) stated on sidewall of tires.
- Place the Forward/Reverse handle in the NEUTRAL position engage the neutral lock, see page 5 - 11.
- Turn the fuel shut-off valve to the closed (OFF) position.
- With proper ventilation, run engine until the remaining fuel in carburetor and fuel lines is depleted and the engine stalls.
- Return the neutral lock to the OPERATE position
- Loosen, but do not remove the carburetor drain screw. Drain any fuel remaining in bowl into an approved container and pour the fuel collected into the vehicle fuel tank. Add Sea Foam (4 oz. for a full tank of fuel) to stabilize fuel and install the tank cap securely.
- Tighten the carburetor drain screw.
- Remove spark plug and pour about 1/2 oz. (15 ml) of SAE 10 - 30 weight oil or Fogging oil into the cylinder. Rotate the crankshaft by hand several times, then install the spark plug.
- Do not engage the park brake, but secure the car from rolling
- While engine is still warm, change oil.
- Clean body, chassis and engine of debris, mud, chaff or grass.



# MAINTENANCE

Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.

## PERIODIC SERVICE SCHEDULE

✓ Check    ♦ Clean, Adjust, etc.    ▲ Replace

To perform service that is listed in this schedule but not described in this manual, contact a local Service Representative or see the Repair and Service Manual for this vehicle.

**NOTE:** Some maintenance items must be serviced more frequently on vehicles used under severe driving conditions

### DAILY

#### BEFORE USE:

- ✓ Check service brake general operation
- ✓ Check park brake operation - does it hold on a hill.
- ✓ Check warning device function in reverse
- ✓ Check tire pressure, condition of tires & rims.
- ✓ Check smooth operation of accelerator.
- ✓ Check for loose or missing hardware.
- ✓ Check Battery - state of charge, condition, loose terminals, corrosion, hold down & hardware
- ✓ Check overall vehicle condition

### WEEKLY (includes items listed in previous table & the following)

|                        |                                                                                          |
|------------------------|------------------------------------------------------------------------------------------|
| TIRES                  | ✓ Examine for cuts, excessive wear and pressure (See GENERAL SPECIFICATIONS)             |
| WHEELS                 | ✓ Check for bent rims, missing or loose lug nuts                                         |
| COOLING FAN            | ✓ Check for build-up of foreign matter inside blower housing and fins, clean if required |
| ENGINE OIL             | ✓ Check and add if required - DO NOT OVERFILL                                            |
| STARTER/GENERATOR BELT | ✓ Check for tension, wear, cracks                                                        |

### MONTHLY - 20 HOURS (includes items listed in previous table & the following)

|                                      |                                                                                          |
|--------------------------------------|------------------------------------------------------------------------------------------|
| WIRING                               | ✓ Check all wiring for loose connections and broken/missing insulation                   |
| ACCELERATOR                          | ✓ Check for smooth movement - DO NOT LUBRICATE CABLE                                     |
| SERVICE BRAKE<br>(MECHANICAL BRAKES) | ✓ Conduct brake performance test                                                         |
| PARK BRAKE                           | ✓ Check brake performance and adjust if required                                         |
| CHOKE CABLE                          | ✓ Check for smooth movement and adjustment - DO NOT LUBRICATE CABLE                      |
| CARBURETOR LINKAGE                   | ✓ Check attachment, adjust as required                                                   |
| DIRECTION SELECTOR                   | ✓ Check attachment, adjust as required                                                   |
| ENGINE                               | ✓ Check for unusual noise, vibration, acceleration, oil leaks                            |
| COOLING FAN                          | ✓ Check for build-up of foreign matter inside blower housing and fins, clean if required |
| STEERING ASSEMBLY                    | ✓ Check for abnormal play, tightness of all hardware                                     |
| TIE ROD/LINKAGES                     | ✓ Check for excessive play, bent components or loose connections                         |
| REAR AXLE                            | ✓ Check for leakage, add SAE 30 oil as required                                          |

### QUARTERLY - 60 HOURS (includes items listed in previous tables & the following)

|                          |                                                                                                                                                                                                                                                  |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FRONT AXLE               | ✓ Check for damage to axle and loose or missing hardware                                                                                                                                                                                         |
| FRONT SHOCK ABSORBERS    | ✓ Check for oil leakage and loose fasteners                                                                                                                                                                                                      |
| FRONT SPRINGS            | ✓ Check for loose hardware, cracks at attachments                                                                                                                                                                                                |
| FRONT WHEEL ALIGNMENT    | ✓ Check for unusual tire wear, align if required                                                                                                                                                                                                 |
| PARK BRAKE               | <ul style="list-style-type: none"> <li>✓ Check for bent/binding linkage rod</li> <li>✓ Check for damage or wear to latch arm or catch bracket</li> <li>♦ Lubricate as required, use light oil. DO NOT LUBRICATE CABLES OR BRAKE LATCH</li> </ul> |
| REAR SHOCK ABSORBERS     | ✓ Check for oil leakage, loose mounting hardware                                                                                                                                                                                                 |
| ENGINE ELECTRICAL SYSTEM | ✓ Check coil/spark plug wires for cracks/loose connections                                                                                                                                                                                       |

#### Periodic Service Schedule

# MAINTENANCE

Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.

|                                                                                               |                                                                                                                                                                                                                                                                        |
|-----------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FUEL SYSTEM                                                                                   | <ul style="list-style-type: none"> <li>✓ Check for leaks at tank, cap, system lines, filters, pump, carburetor</li> <li>✓ Check system lines for cracks/deterioration</li> </ul>                                                                                       |
| THROTTLE/GOVERNOR LINKAGE                                                                     | <ul style="list-style-type: none"> <li>✓ Check operation and governed speed</li> </ul>                                                                                                                                                                                 |
| HARDWARE AND FASTENERS                                                                        | <ul style="list-style-type: none"> <li>✓ Check for loose or missing hardware and components</li> <li>◆ Tighten or replace missing hardware</li> </ul>                                                                                                                  |
| <b>SEMI-ANNUAL - 125 HOURS (includes items listed in previous tables &amp; the following)</b> |                                                                                                                                                                                                                                                                        |
| BATTERY                                                                                       | ◆ Clean battery & terminals                                                                                                                                                                                                                                            |
| DIRECTION SELECTOR                                                                            | ✓ Check for wear and smooth movement (lubricate shaft with light oil if required)                                                                                                                                                                                      |
| KING PINS                                                                                     | ✓ Check for excessive play and tightness of retaining nuts                                                                                                                                                                                                             |
| STEERING ASSEMBLY                                                                             | ✓ Check bellows and pinion seal for damage or grease leakage                                                                                                                                                                                                           |
| RACK END BALL JOINT                                                                           | ◆ Lubricate, use wheel bearing grease                                                                                                                                                                                                                                  |
| REAR AXLE                                                                                     | ✓ Check for unusual noise and loose or missing mounting hardware                                                                                                                                                                                                       |
| AIR FILTER ELEMENT                                                                            | ✓ Check filter element, clean/replace as required                                                                                                                                                                                                                      |
| OIL FILTER                                                                                    | ▲ Replace (at oil change)                                                                                                                                                                                                                                              |
| ENGINE OIL                                                                                    | ▲ Replace with SAE 10W-30 or 10W-40 that meets or exceeds SF, SG, CC oil, DO NOT OVERFILL                                                                                                                                                                              |
| DRIVE BELT                                                                                    | ✓ Check for cracks, fraying and excessive wear                                                                                                                                                                                                                         |
| <b>ANNUAL - 250-300 HOURS (includes items listed in previous tables &amp; the following)</b>  |                                                                                                                                                                                                                                                                        |
| FRONT WHEEL BEARINGS                                                                          | ✓ Check and adjust as required, see Technician's Repair and Service Manual                                                                                                                                                                                             |
| REAR AXLE                                                                                     | ✓ Check lubricant, add lubricant as required                                                                                                                                                                                                                           |
| SERVICE BRAKES                                                                                | <ul style="list-style-type: none"> <li>◆ Clean and adjust, see Technician's Repair and Service Manual</li> <li>✓ Check brake shoe linings, see Technician's Repair and Service Manual</li> <li>✓ Check level, add if required (DOT 3) and check for leakage</li> </ul> |
| FUEL FILTER                                                                                   | ▲ Replace                                                                                                                                                                                                                                                              |
| SPARK PLUG                                                                                    | ▲ Replace, gap new plug                                                                                                                                                                                                                                                |
| MUFFLER/EXHAUST                                                                               | ✓ Check mounting hardware; check for leaks at head and muffler gaskets                                                                                                                                                                                                 |
| VALVES                                                                                        | ✓ Check cold (intake/exhaust) per Technician's Repair and Service Manual                                                                                                                                                                                               |
| <b>500 HOURS (includes items listed in previous tables &amp; the following)</b>               |                                                                                                                                                                                                                                                                        |
| CARBURETOR                                                                                    | ◆ Clean                                                                                                                                                                                                                                                                |
| CYLINDER HEAD AND PISTON                                                                      | <ul style="list-style-type: none"> <li>◆ Remove carbon from cylinder head and piston</li> <li>✓ Check valve seats for carbon buildup and clean as required</li> </ul>                                                                                                  |

## Periodic Service Schedule

# MAINTENANCE

Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.

## Capacities and Replacement Parts

|                               |                                                              |
|-------------------------------|--------------------------------------------------------------|
| Fuel Tank / Fuel              | 5.3 gal (20.0 liters) / 87 Octane Min                        |
| Engine Oil                    | 1.4 US qt (1.3 liters)                                       |
| Oil Filter                    | P/N 607454                                                   |
| Air Filter                    | P/N 28463G01                                                 |
| Spark Plug                    | NGK BPR2ES (P/N 607462)<br>.028" - .031" (.7 mm - .8 mm) Gap |
| Starter/Generator Belt        | P/N 26414G1                                                  |
| Clutch Belt                   | P/N 618630                                                   |
| Rear Axle Oil                 | 51 oz (1.5 liters) / SAE 30                                  |
| Fuse                          | 15 amp (P/N 18392G1)                                         |
| LED Bulb                      | (P/N 619101)                                                 |
| Headlight Bulb                | (P/N 619100)                                                 |
| Turn Signal Bulb              | (P/N 619102)                                                 |
| Tail Light Bulb               | #1157 (P/N 611242)                                           |
| Friction Modifier (Rear Axle) | 2 oz (60 mL) (P/N 625753)                                    |

## HARDWARE

Periodically, the vehicle should be inspected for loose fasteners. Fasteners should be tightened in accordance with the Torque Specifications table

Use care when tightening fasteners and refer to the Technician's Repair and Service Manual for specific torque values.

Generally, three grades of hardware are used in the vehicle. Grade 5 hardware can be identified by the three marks on the hexagonal head and grade 8 hardware is identified by 6 marks on the head. Unmarked hardware is Grade 2.

| <b>ALL TORQUE FIGURES ARE IN FT. LBS. (Nm)</b><br>Unless otherwise noted in text, tighten all hardware in accordance with this chart.<br>This chart specifies 'lubricated' torque figures. Fasteners that are plated or lubricated when installed are considered 'wet' and require approximately 80% of the torque required for 'dry' fasteners. |          |            |            |            |             |              |              |              |              |              |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|------------|------------|------------|-------------|--------------|--------------|--------------|--------------|--------------|
| BOLT SIZE                                                                                                                                                                                                                                                                                                                                        | 1/4"     | 5/16"      | 3/8"       | 7/16"      | 1/2"        | 9/16"        | 5/8"         | 3/4"         | 7/8"         | 1"           |
| Grade 2                                                                                                                                                                                                                                                       | 4<br>(5) | 8<br>(11)  | 15<br>(20) | 24<br>(33) | 35<br>(47)  | 55<br>(75)   | 75<br>(102)  | 130<br>(176) | 125<br>(169) | 190<br>(258) |
| Grade 5                                                                                                                                                                                                                                                       | 6<br>(8) | 13<br>(18) | 23<br>(31) | 35<br>(47) | 55<br>(75)  | 80<br>(108)  | 110<br>(149) | 200<br>(271) | 320<br>(434) | 480<br>(651) |
| Grade 8                                                                                                                                                                                                                                                       | 6<br>(8) | 18<br>(24) | 35<br>(47) | 55<br>(75) | 80<br>(108) | 110<br>(149) | 170<br>(230) | 280<br>(380) | 460<br>(624) | 680<br>(922) |
| BOLT SIZE                                                                                                                                                                                                                                                                                                                                        | M4       | M5         | M6         | M8         | M10         | M12          | M14          |              |              |              |
| Class 5.8<br>(Grade 2)                                                                                                                                                                                                                                        | 1<br>(2) | 2<br>(3)   | 4<br>(6)   | 10<br>(14) | 20<br>(27)  | 35<br>(47)   | 55<br>(76.4) |              |              |              |
| Class 8.8<br>(Grade 5)                                                                                                                                                                                                                                        | 2<br>(3) | 4<br>(6)   | 7<br>(10)  | 18<br>(24) | 35<br>(47)  | 61<br>(83)   | 97<br>(131)  |              |              |              |
| Class 10.9<br>(Grade 8)                                                                                                                                                                                                                                       | 3<br>(4) | 6<br>(8)   | 10<br>(14) | 25<br>(34) | 49<br>(66)  | 86<br>(117)  | 136<br>(184) |              |              |              |

Ref Tsp 1

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## Notes:

# MAINTENANCE

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

Notes:

5

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

TABLE OF CONTENTS FOR APPENDIX A

| TITLE                           | PAGE NO. |
|---------------------------------|----------|
| DECLARATION OF CONFORMITY ..... | A - 3    |

# APPENDIX A

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## Notes:

Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.

## DECLARATION OF CONFORMITY

DECLARATION OF CONFORMITY • ДЕКЛАРАЦИЯ ЗА СЪОТВЕТСТВИЕ • PROHLÁŠENÍ O SHODĚ •  
OVERENSSTEMMELSESERKLÆRING • CONFORMITEITSVERKLARING • VASTAVUSDEKLARATSIOON •  
VAATIMUSTENMUKAISUUSVAKUUTUS • DECLARATION OF CONFORMITE • KONFORMITÄTSEKTLÄRUNG • ΔΗΛΩΣΗ  
ΣΥΜΜΟΡΦΩΣΗΣ • MEGFELELŐSÉGI NYILATKOZAT • DICHIARAZIONE DI CONFORMITÀ • ATBILSTĪBAS DEKLARĀCIJA •  
ATITIKTIES DEKLARACIJA • DIKJARAZZJONI TAL-KONFORMITÀ • DEKLARACJA ZGODNOŚCI • DECLARAÇÃO DE  
CONFORMIDADE • DECLARAȚIE DE CONFORMITATE • VYHLÁŠENIE O ZHODE • IZJAVA O SKLADNOSTI • DECLARACIÓN  
DE CONFORMIDAD • DEKLARATION OM ÖVERENSSTÄMMELSE • SAMRÆMISYFIRLÝSING • KONFORMITETSEKTLÆRING

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                                                                                                                                                                                                                                  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Business name and full address of the manufacturer • Търговско име и пълен адрес на производителя •<br>Obchodní jméno a plná adresa výrobce • Producentens firmanavn og fulde adresse • Bedrijfsnaam en volledige adres van de fabrikant • Tootja ärinimi ja täielik aadress •<br>Valmistajan toiminimi ja täydellinen osoite • Nom commercial et adresse complète du fabricant • Firmenname und vollständige Adresse des Herstellers • Εταιρικό και<br>ταχυδρομική διεύθυνση κατασκευαστή • A gyártó üzleti neve és teljes címe • Ragione sociale e indirizzo completo del fabbricante • Uzņēmuma nosaukums un pilna<br>ražotāja adrese • Verslo pavadinimas ir pilnas gamintojo adresas • Išem kumertjāli u indirizz shh tal-fabbrikant • Nazwa firmy i pełny adres producenta • Nome da<br>empresa e endereço completo do fabricante • Denumirea comercială și adresa completă a producătorului • Obchodný názov a úplná adresa výrobcu • Naziv podjetja in<br>polni naslov proizvajalca • Nombre de la empresa y dirección completa del fabricante • Tillverkarens företagsnamn och kompletta adress • Fyrirtækishelti og fullt<br>heimilisfang framleiðanda • Firmanavn og full address for produsenten | E-Z-Go Division of Textron Inc,<br>1451 Marvin Griffin Road<br>Augusta, GA 30906 USA                                                                                                                                                                                                             |
| Product Code • Код на продукта • Kód výrobku • Produktcode • Productcode • Toote kood • Tuotekoodi • Code produit • Produktcode • Кодовый продукт • Termékkód •<br>Codice prodotto • Produkta kodas • Produkti kodas • Kodici tal-Prodott • Kod produktu • Código do Produto • Cod produs • Kód výrobku • Oznaka proizvoda • Código de<br>producto • Produktkod • Vörunúmer • Produktkode                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 605785, 76211, 606697, 605815, 605811,<br>606688, 605782, 606698, 617791, 615793,<br>606695, 617795 and 617793, 617340, 618846,<br>618847, 618855, 618856, 618859, 618860,<br>and 618866 when fitted with CE Kit 614168.<br>618862, 618864, 619213 and 617795 when<br>fitted with CE KIT 625759. |
| Machine Name • Наименование на машината • Název stroje • Maskinnavn • Machinenam • Masina nimi • Laitteen nimi • Nom de la machine • Maschinenbezeichnung •<br>Όνομασία μηχανήματος • Gépnev • Denominazione della macchina • Iekārtas nosaukums • Mašinos pavadinimas • Išem tal-Magna • Nazwa urządzenia • Nome da<br>Máquina • Numele echipamentului • Názov stroja • Naziv stroja • Nombre de la máquina • Maskinens namn • Heiti tækis • Maskinnavn                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | ST, Hauler, Terrain, Express Sx, Lx, and<br>Shuttle 4X_G utility vehicle (gasoline<br>models).<br>E-Z-Go, Cushman or<br>Bad Boy Buggies brands.                                                                                                                                                  |
| Designation • Предназначение • Označení • Betegnelse • Benaming • Nimetus • Typymerkintä • Pažymėjimas •<br>Bezeichnung • Χαρακτηρισμός • Megnevezés • Funzione • Apzīmējums • Lithuanian • Denominazzjoni • Oznaczenie •<br>Designação • Specificație • Označenie • Namen stroja • Descripción • Beteckning • Merking • Konstruksjon                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Utility Vehicle                                                                                                                                                                                                                                                                                  |
| Serial Number • Серийн номер • Sériové číslo • Seriennummer • Seriennummer • Seerianumber • Valmistusnumero • Numéro de série • Seriennummer • Σειριακός αριθμός •<br>Sorozatszám • Numero di serie • Sérijas numurs • Serijos numeris • Numur Serjali • Numer serjiny • Número de Série • Număr de serie • Sériové číslo • Serijska številka •<br>Número de série • Seriennummer • Raðnúmer • Seriennummer                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 27400976 to 3200000 or 8003600-8009600.                                                                                                                                                                                                                                                          |
| Conforms to Directives • В съответствие с директивите • Splňuje podmínky směrnic • Er i overensstemmelse med direktiver • Voldoet aan de richtlijnen • Vastab<br>direktiividele • Direktiivien mukainen • Conforme aux directives • Entspricht Richtlinien • Ακολουθεί τις Οδηγίες • Megfelel az irányelveknek • Conforme alle<br>Directive • Atbilst direktīvām • Atitinka direktyvų reikalavimus • Valutazzjoni tal-Konformità • Dyrektyw związane • Cumpre as Directivas • Respectă Directivele • Je v<br>súlade so smernicami • Skladnost z direktivami • Cuple con las Directivas • Uppfyller direktiv • Samræmist tilskipunum • I samsvar med direktiv                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 2006/42/EC                                                                                                                                                                                                                                                                                       |
| Conformity Assessment • Оценка за съответствие • Hodnocení plnění podmínek • Overensstemmelsesvurdering •<br>Conformiteitsbeoordeling • Vastavushindamine • Vaatimustenmukaisuuden arviointi • Evaluation de conformité •<br>Konformitätsbeurteilung • Δοκιμώση Συμμόρφωσης • Megfelelőség-értékelés • Valutazione della conformità •<br>Atbilstības novērtējums • Atitikties įvertinimas • Liveli tal-Qawwa tal-Foss Imkejjel • Ocena zgodności •<br>Avaliação de Conformidade • Evaluarea conformității • Vyhodnotenie zhodnosti • Ocena skladnosti •<br>Evaluación de conformidad • Bedömning av överensstämmelse • Samræmistat • Konformitetsvurdering                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 2006/42/EC Annex II                                                                                                                                                                                                                                                                              |
| Harmonised standards used • Използвани хармонизирани стандарти • Použité harmonizované normy • Brugte harmoniserede standarder • Gebruikte geharmoniseerde<br>standaards • Kasutatud ühtlustatud standardid • Käytetyt yhdenmukaistettut standardit • Normes harmonisées utilisées • Angewandte harmonisierte Normen •<br>Ευρωπαϊσόμενα πρότυπα που χρησιμοποιήθηκαν • Harmonizált szabványok • Standard armonizzati applicati • Izmantotie saskaņotie standarti • Panaudoti suderinti<br>standartai • Standards armonizzati usati • Normy spójne powiązane • Normas harmonizadas usadas • Standardele armonizate utilizate • Použité harmonizované normy •<br>Uporabljeni usklajeni standardi • Estándares armonizados utilizados • Harmoniserade standarder som används                                                                                                                                                                                                                                                                                                                                                                                                                                    | EN 61000-6-2:2005<br>EN 61000-6-4:2007<br>EN ISO 5349:2001<br>EN ISO 11202: 1995                                                                                                                                                                                                                 |
| Technical standards and specifications used • Използвани технически стандарти и спецификации •<br>Použité technické normy a specifikace • Brugte tekniske standarder og specifikationer •<br>Gebruikte technische standaards en specificaties • Kasutatud tehnilised standardid ja spetsifikatsioonid •<br>Käytetyt tekniset standardit ja eritelmit • Spécifications et normes techniques utilisées •<br>Angewandte technische Normen und Spezifikationen • Τεχνικά πρότυπα και προδιαγραφές που χρησιμοποιήθηκαν • Műszaki szabványok és specifikációk • Standard<br>tecnic e specifice aplicati •<br>Izmantotie tehnicie standarti un specifikācijas • Panaudoti techniniai standartai ir techninė informacija •<br>Standards u specifikacijonijiet tehnici užati • Normy i specifikacje techniczne powiązane •<br>Normas técnicas e especificações usadas • Standardele tehnice și specificațiile utilizate •<br>Použité technické normy a specifikácie • Uporabljeni tehnični standardi in specifikacije •<br>Estándares y especificaciones técnicas utilizadas • Tekniska standarder och specifikationer som används • Samræmdir staðlar sem notaðir eru • Benyttede harmoniseret<br>standarder        | ISO 2631-1:1997                                                                                                                                                                                                                                                                                  |
| The place and date of the declaration • Място и дата на декларацията • Misto a datum prohlášení • Sted og dato for erklæringen • Plaats en datum van de verklaring •<br>Deklaratsiooni väljastamise koht ja kuupäev • Vakuutuksen paikka ja päivämäärä • Lieu et date de la déclaration • Ort und Datum der Erklärung • Τόπος και ημερομηνία<br>δηλώσεως • A nyilatkozat kelte (hely és idő) • Luogo e data della dichiarazione • Deklarācijas vieta un datums • Deklaracijos vieta ir data • Li-post u d-data tad-dikjarazzjoni •<br>Miejsce i data wystawienia deklaracji • Local e data da declaração • Locul și data declarăției • Miesto a dátum vyhlásenia • Kraj in datum izjave • Lugar y fecha de la<br>declaración • Plats och datum för deklarationen • Tæknistaðlar og tæknilysingar sem notaðar eru • Benyttede tekniske standarder og specifikasjoner • Staður og<br>dagsetning yfirlýsingar • Sted og dato for erklæringen                                                                                                                                                                                                                                                                    | E-Z-Go Division of Textron Inc,<br>1451 Marvin Griffin Road<br>Augusta, GA 30906 USA                                                                                                                                                                                                             |

# APPENDIX A

Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.

## DECLARATION OF CONFORMITY (CONTINUED)

Signature of the person empowered to draw up the declaration on behalf of the manufacturer, holds the technical documentation and is authorised to compile the technical file, and who is established in the Community.

Подпис на човека, упълномощен да състави декларацията от името на производителя, който поддържа техническата документация и е оторизиран да изготви техническия файл и е регистриран в общността. Podpis osoby oprávněné sestavit prohlášení jménem výrobce, držet technickou dokumentaci a osoby oprávněné sestavit technické soubory a založené v rámci Evropského společenství.

Underskrift af personen, der har fuldmagt til at udarbejde erklæringen på vegne af producenten, der er indehaver af dokumentationen og er bemyndiget til at udarbejde den tekniske journal, og som er baseret i nærområdet. Handtekening van de persoon die bevoegd is de verklaring namens de fabrikant te tekenen, de technische documentatie bewaart en bevoegd is om het technische bestand samen te stellen, en die is gevestigd in het Woongebied. Ühenduse registreeritud isiku allkiri, kes on volitatud tootja nimel deklaratsiooni koostama, kes omab tehnilist dokumentatsiooni ja kellel on õigus koostada tehniline toimik.

Sen henkilön allekirjoitus, jolla on valmistajan valtuutus vakuutuksen laadintaan, jolla on hallussaan tekniset asiakirjat, joka on valtuutettu laatimaan tekniset asiakirjat ja joka on sijoittautunut yhteisöön.

Signature de la personne habilitée à rédiger la déclaration au nom du fabricant, à détenir la documentation technique, à compiler les fichiers techniques et qui est implantée dans la Communauté.

Unterschrift der Person, die berechtigt ist, die Erklärung im Namen des Herstellers abzugeben, die die technischen Unterlagen aufbewahrt und berechtigt ist, die technischen Unterlagen zusammenzustellen, und die in der Gemeinschaft niedergelassen ist.

Υπογραφή ατόμου εξουσιοδοτημένου για την σύνταξη της δήλωσης εκ μέρους του κατασκευαστή, ο οποίος κατέχει την τεχνική έκθεση και έχει την εξουσιοδότηση να τηγμονοήσει τον τεχνικό φάκελο και ο οποίος είναι διαρισμένος στην Κοινότητα.

A gyártó nevében meghatalmazott személy, akinek jogában áll módosítani a nyilatkozatot, a műszaki dokumentációt őrizi, engedélyvel rendelkezik a műszaki fáj összeállításához, és aki a közösségen belüli letelepedett személy.

Firma della persona autorizzata a redigere la dichiarazione a nome del fabbricante, in possesso Della documentazione tecnica ed autorizzata a costituire il fascicolo tecnico, che deve essere stabilita nella Comunità.

Tās personas paraksts, kura ir pilnvarota deklarācijas sastādīšanai ražotāja vārdā, kurai ir tehniskā dokumentācija, kura ir pilnvarota sagatavot tehnisko reģistru un kura ir apstiprināta Kopienā.

Asmuo, kuris yra gana žinomas, kuriam gamintojas suteikė įgaliojimus sudaryti šią deklaraciją, ir kuris ją pasirašė, turi visą techninę informaciją ir yra įgaliojamas sudaryti techninės informacijos dokumentą.

Il-firma tal-persuna awtorizzata li fassoli id-dikjarazzjoni fil-fabbrikant, għandha d-dokumentazzjoni teknika u hija awtorizzata li tikkompila l-fajl tekniku u li hija stabbilita fil-Komunità.

Podpis osoby upoważnionej do sporządzenia deklaracji w imieniu producenta, przechowującej dokumentację techniczną, upoważnioną do stworzenia dokumentacji technicznej oraz wyznaczonych ds. wapólotowych.

Assinatura da pessoa com poderes para emitir a declaração em nome do fabricante, que possui a documentação técnica, que está autorizada a compilar o processo técnico e que está estabelecida na Comunidade.

Semnătura persoanei împuternicite să elaboreze declarația în numele producătorului, care deține documentația tehnică, este autorizată să compileze dosarul tehnic și este stabilită în Comunitate.

Podpis osoby poverenej vystavením vyhlásenia v mene výrobcu, ktorá má technickú dokumentáciu a je oprávnená spracovať technické podklady a ktorá je umiestnená v Spoločenstve.

Podpis osebe, pooblaščené za izdelavo izjave v imenu proizvajalca, ki ima tehnično dokumentacijo in lahko sestavlja spis tehnične dokumentacije, ter ima sedež v Skupnosti.

Firma de la persona responsable de la declaración en nombre del fabricante, que posee la documentación técnica y está autorizada para recopilar el archivo técnico y que está establecido en la Comunidad.

Undertecknas av den som bemyndigad att upprätta deklarationen å tillverkarens vägnar, innehar den tekniska dokumentationen och är bemyndigad att sammanställa den tekniska informationen och som är etablerad i gemenskapen.

Undirskrift aðilans sem hefur umboð til að gera yfirlýsinguna fyrir hönd framleiðandans, hefur undir höndum tæknigögn og hefur leyfi til að taka saman tækniskýrsluna, og er víðurkenndur innan evrópska efnahagssvæðisins.

Signaturen til personen som har fuldmagt til å udfærdige erklæringen på vegne af producenten, er i besiddelse af den tekniske dokumentationen, har autorisasjon til å utarbeide den tekniske filen og som har tilhold i EU.

2006/42/EC Annex II 1A: 2

Tim Lansdell

Technical Director

06th October 2011

Ransomes Jacobsen

Ltd, West Road, Ransomes Europark,  
Ipswich,  
England, IP3 9TT



2006/42/EC Annex II 1A: 10

Christopher W. Spencer

Vice President of Engineering

E-Z-GO Division of Textron Inc,

1451 Marvin Griffin Road

Augusta, GA 30906 USA

06th October 2011

GB

United Kingdom

BG

Bulgaria

CH

Switzerland

CZ

Czech Republic

DK

Denmark

NL

Netherlands

EE

Estonia

ES

Spain

FI

Finland

FR

France

DE

Germany

GR

Greece

HU

Hungary

IS

Iceland

IT

Italy

LI

Liechtenstein

LV

Latvia

LT

Lithuania

MT

Malta

NO

Norway

PL

Poland

PT

Portugal

RO

Romania

SE

Sweden

SK

Slovakia

SI

Slovenia

**Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.**

## Notes:

# APPENDIX A

*Read all of this manual to become thoroughly familiar with this vehicle. Pay particular attention to all Notices, Cautions, Warnings, and Dangers.*

## Notes:





A Textron Company

**E-Z-GO Division of Textron Inc.,**  
1451 Marvin Griffin Road, Augusta, Georgia 30906 - 3852 USA

**TO CONTACT US...**

**North America:**

**Technical Assistance & Warranty**

Phone: 1-800-774-3946, FAX: 1-800-448-8124

**Service Parts**

Phone: 1-888-GET-E-Z-GO (1-888-438-3946), FAX: 1-800-752-6175

**International:**

Phone: 001-706-798-4311, FAX: 001-706-771-4609

Service Parts Manuals, as well as Repair and Service Manuals  
are available from a local Distributor, an authorized Branch,  
Genuine E-Z-GO Parts & Accessories Department or at [www.shopezgo.com](http://www.shopezgo.com).

Copyrighted Material  
This manual may not be reproduced in whole or  
in part without the express permission of  
E-Z-GO Division of Textron Inc.  
Technical Communications Department