



## E-Z-GO® EXPRESS™ L6

### OFF-ROADING FOR THE FAMILY.

The more the merrier. With four forward-facing and two rear-facing seats, the entire family will always be ready to ride with the E-Z-GO® Express™ L6. Its eco-friendly powertrain options, rugged tires and higher ground clearance meet a smooth ride and stylish lines to deliver you where you want to be, even off the beaten path.



A Textron Company



# E-Z-GO EXPRESS L6

Uneven terrain, unimproved roads, rutted or pitted trails to the lake — the E-Z-GO Express L6 handles it all in impressive fashion. Choose from best-in-class 13.5-hp Kawasaki® gas-powered engine or quiet, zero-emissions 48-volt electric drivetrain. Add the optional limited slip differential for better traction in wet or slippery conditions, and enjoy all of the ergonomic features and extras the L6 provides.



Two-Tone Seats



Front Brush Guard



Optional  
Fold-Down Windshield



Fold-Down Cargo Deck



Taillights

## OUR COMMITMENT TO **green**

- ▶ Electric model features quiet, zero-emissions 48-volt electric drivetrain
- ▶ Gas-powered model features a 13.5-hp Kawasaki® engine with hemispheric combustion chamber for better fuel economy (exceeds EPA/CARB standards)
- ▶ Foam seating made of 100% recycled materials
- ▶ Repaired surface design requires less water when cleaning
- ▶ Recyclable plastic components
- ▶ Manufactured in ISO 14001-certified facility



A Textron Company

### STANDARD FEATURES

- ▶ 23-in trail tires
- ▶ Alloy wheels
- ▶ Two-tone seats
- ▶ Front brush guard
- ▶ Headlights & taillights
- ▶ Brake lights
- ▶ Fold down cargo deck
- ▶ Cupholders
- ▶ Dashboard storage pockets
- ▶ Low oil indicator (gas only)
- ▶ Fuel gauge (gas only)
- ▶ State of charge meter (electric only)

### POPULAR OPTIONS & ACCESSORIES

- ▶ Fold-down windshield
- ▶ Roof
- ▶ Woodside stake cargo bed (replaces rear-facing seat)
- ▶ Roto-molded plastic bed (replaces rear-facing seat)
- ▶ Comfort grip steering wheel
- ▶ High-output LED headlights
- ▶ Turn signals w/ 4-way flashers
- ▶ Hour meter
- ▶ Limited slip differential
- ▶ Clays Car™ field kit
- ▶ 2-in (5 cm) front hitch receiver
- ▶ Rear fender flares
- ▶ Ashtray
- ▶ CE kit (gas only)
- ▶ 12-volt accessory outlet (gas only)
- ▶ DC/DC converter (electric only)
- ▶ Battery watering system (electric only)
- ▶ 48-volt battery charger (electric only)



FRONT



BACK



## ELECTRIC

## GAS

	ELECTRIC	GAS
<b>DIMENSIONS</b>		
Overall Length	143.5 in (364 cm)	143.5 in (364 cm)
Overall Width	48.5 in (123 cm)	48.5 in (123 cm)
Overall Height (w/o roof)	52.5 in (133 cm)	52.5 in (133 cm)
Overall Height (w/ roof)	76.5 in (194 cm)	76.5 in (194 cm)
Wheel Base	95.0 in (241 cm)	95.0 in (241 cm)
Front Wheel Track	37.5 in (95 cm)	37.5 in (95 cm)
Rear Wheel Track	38.5 in (98 cm)	38.5 in (98 cm)
Ground Clearance @ Differential	7.0 in (18 cm)	7.0 in (18 cm)
<b>POWER</b>		
Power Source	48 Volt DC	4-Cycle 24.5 cu in (401cc) Low-Emissions
Valve Train	N/A	Single Cylinder OHV
Motor Type	Shunt Wound	N/A
Horsepower (kW)	2.5 hp (1.9 kW) Continuous	13.5 hp (10.1 kW) Exceeds SAE J1940 Std
Electrical System	48 Volt	Starter/Generator — Solid State Regulator
Batteries (qty/type)	Eight, 6 Volt Deep Cycle	One, 12 Volt Maintenance Free
Key or Pedal Start	Pedal	Pedal
Air Cleaner	N/A	Replaceable Dry Cartridge
Lubrication	N/A	Pressurized Oil System
Oil Filter	N/A	Spin-On
Cooling System	N/A	Air Cooled
Fuel Capacity	N/A	5.8 Gallon (22.0 L)
Battery Charger	48 VDC Delta Q, 120/230 VAC, UL & CSA	N/A
Speed Controller	400 Amp	N/A
Drivetrain	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)
Transaxle	Differential with Helical Gears	Differential with Helical Gears
Gear Selection	Dash Mounted Forward-Neutral-Reverse	Forward-Reverse
Rear Axle Ratio	14.7:1	11.42:1 (Forward), 15.78:1 (Reverse)
<b>PERFORMANCE</b>		
Seating Capacity	6-Passenger (4-Passenger with Optional Cargo Bed)	6-Passenger (4-Passenger with Optional Cargo Bed)
Dry Weight (w/o batteries)	720 lb (325 kg)	970 lb (445 kg)
Curb Weight	1,210 lb (545 kg)	1,020 lb (465 kg)
Vehicle Load Capacity	1,198 lb (540 kg)	1,200 lb (540 kg)
Outside Clearance Circle	25.5 ft (7.8 m)	25.5 ft (7.8 m)
Intersecting Aisle Clearance	6.5 ft (1.98 m)	6.5 ft (1.98 m)
Speed (level ground)	16.0 mph $\pm$ 0.5 mph (26.0 kph $\pm$ 0.8 kph)	16.0 mph $\pm$ 0.5 mph (25.7 kph $\pm$ 0.8 kph)
<b>STEERING &amp; SUSPENSION</b>		
Steering	Self-Compensating Reduction Rack and Pinion	Self-Compensating Reduction Rack and Pinion
Suspension	Leaf Springs with Hydraulic Shock Absorbers	Leaf Springs with Hydraulic Shock Absorbers
Service Brake	Rear Wheel Mechanical Self-Adjusting Drum	Rear Wheel Mechanical Self-Adjusting Drum
Parking Brake	Self-Compensating, Single Point Engagement	Self-Compensating, Single Point Engagement
Tires	Trail Tires 23x10.5-12, Alloy Wheel	Trail Tires 23x10.5-12, Alloy Wheel
<b>BODY &amp; CHASSIS</b>		
Frame	Welded Steel with DuraShield™ Powder Coat	Welded Steel with DuraShield™ Powder Coat
Body & Finish	Injection Molded TPO	Injection Molded TPO
Standard Body Color	Black	Black
Optional Body Colors	Electric Blue, Flame Red, Hunter Green, Ivory, Yellow, Orange, Bright White, Platinum, Inferno Red, Metallic Charcoal, Patriot Blue, Steel Blue (custom colors also available)	Electric Blue, Flame Red, Hunter Green, Ivory, Yellow, Orange, Bright White, Platinum, Inferno Red, Metallic Charcoal, Patriot Blue, Steel Blue (custom colors also available)
Standard Seat Color	Red on Black	Red on Black
Optional Seat Colors	White on Red, White on Blue, Black, Tan, Oyster (custom colors also available)	White on Red, White on Blue, Black, Tan, Oyster (custom colors also available)



A Textron Company

Features and specifications of vehicles subject to change without notice. Vehicles as photographed may include options not included on base model. ©2011 E-Z-GO Division of Textron Inc. All rights reserved. 82300-G1